

TTMA Flange x Cam & Groove Couplings

Application:	Used to connect dry bulk product hoses; the TTMA flange x cam and groove allows product hoses to be connected directly to the dry bulk tanker piping system.
Standards:	Interchanges with all product produced to commercial item description A-A-59326B. Flange connections are manufactured to connect with the TTMA (Tank Truck Manufacturers Association) flange pattern, see page 9 for flange dimensions.
Materials:	Aluminum, Buna cam and groove gaskets
Features & Benefits:	<ul style="list-style-type: none"> • Precision machined to rigid tolerances • Durable stainless steel cam arm pins will not rust or bind, for greater strength and safety • Recess holds gasket firmly in place - ensures proper placement



300-ALT-AL



300-DLT-AL



40022ALTAL



40022DLTAL

Part #	Description
300-ALT-AL¹	3" TTMA flange x 3" cam and groove adapter (straight)
3040ALTAL	3" TTMA flange x 4" cam and groove adapter (straight)
400-ALT-AL¹	4" TTMA flange x 4" cam and groove adapter (straight)
40022ALTAL	4" TTMA flange x 4" cam and groove adapter (22½°)
600-ALT-AL	6" TTMA flange x 6" cam and groove adapter (straight)
300-DLT-AL	3" TTMA flange x 3" cam and groove coupler (straight)
3040DLTAL	3" TTMA flange x 4" cam and groove coupler (straight)
400-DLT-AL	4" TTMA flange x 4" cam and groove coupler (straight)
40022DLTAL	4" TTMA flange x 4" cam and groove coupler (22½°)
600-DLT-AL	6" TTMA flange x 6" cam and groove coupler (straight)

¹ 300-ALT-AL and 400-ALT-AL are also available in 316 stainless steel

- See page 9 for TTMA flange gaskets.