

### Red Plain Hose Nozzles

**Specification**

- Maximum operating pressure: **100 PSI** (water only) at 70°F (21°C)

Size	Thread	Length	Orifice	Polycarbonate Part #
1-1/2"	NPSH	10"	1/2"	PN15
	NST (NH)			PN15F



### UL Play Pipes with Tip

**Application**

- Often required in hydrant houses by insurance underwriters

**Features**

- Swivel handle, red marlin trim
- Comes standard with 1-1/8" orifice tip

**Specification**

- Maximum operating pressure: **100 PSI** (water only) at 70°F (21°C)

**Approvals**

- UL listed and Factory Mutual approved
- ULT male thread specification: 2-3/16" ODM x 12 TPI

Size	Female Thread	Male Thread	Overall Length	Brass Part #
2-1/2"	NST (NH)	ULT	30"	UPP250F
				playpipe only



### Tips

**Feature**

- Finish: satin

**Specification**

- Maximum operating pressure: **100 PSI** (water only) at 70°F (21°C)

**Approval**

- ULT male thread specification: 2-3/16" ODM x 12 TPI

Orifice	Cast Brass Part #
1-1/8"	UPPT
1-1/4"	UPPT125
1-1/2"	UPPT150
1-3/4"	UPPT175



### Street Cleaning Nozzles

**Feature**

- Welded fabrication

Size	Connection	Aluminum Part #
2"	female cam	200DBAL
3"	female cam	300DBAL

