

Air King®

⚠ WARNING

- The use of an Air King safety clip or wire type retainer is necessary to ensure Air King universal couplings will not become accidentally disconnected. This guarantees the fittings are properly connected because the safety pin will not go through the holes in mating flanges until couplings are locked in place. Only one Air King safety clip or wire type retainer is required for each Air King universal coupling.


Features

- Can be used with Air King ferrules
- Supplied with safety clip
- Supplied with rubber washers, part # AWR4

Specifications

- Pressure rating: **150 PSI** at ambient temperature **70°F (21°C)**
- Meets pressure requirements as specified in A-A-59553 commercial item description superseding Mil Spec.WWC-633D

2-Lug Hose Ends



Size	Iron Part #	Optional Qty	Brass Part #	Optional Qty	316 Stainless Steel Part #
3/8"	AMH ¹	25	GABH ¹	25	RAMH
1/2"	AM1	50	GAB1 ¹	50	RAM1
5/8"	AM5	50	AB5	50	---
3/4"	AM6	50	GAB6 ¹	50	RAM6
1"	AM11	50	GAB11 ¹	50	RAM11

2-Lug Male NPT Ends




Size	Iron Part #	Optional Qty	Brass Part #	Optional Qty	316 Stainless Steel Part #
1/4"	AMB1	25	ABB1	25	---
3/8"	AMB	25	ABB	25	RAMB
1/2"	AM2	50	GAB2 ¹	50	RAM2
3/4"	AM7	50	GAB7 ¹	50	RAM7
1"	AM12	50	GAB12 ¹	50	RAM12

2-Lug Female NPT Ends



Size	Iron Part #	Optional Qty	Brass Part #	Optional Qty	316 Stainless Steel Part #
1/4"	AMC1	25	ABC1	25	---
3/8"	AMC	25	ABC	25	RAMC
1/2"	AM3	50	GAB3 ¹	50	RAM3
3/4"	AM8	50	GAB8 ¹	50	RAM8
1"	AM13	50	GAB13 ¹	50	RAM13

¹ Global investment cast

NOTE: Air King is for air and water service only, Warning: Never use any Air King coupling for steam service! None of Dixon's catalog information is to be interpreted to mean that this type of coupling is suitable for use on steam hose. 

E