

D.O.T. Push-In Fittings

Features

- Materials:
 - Body (straights) tube, supports and grippers: brass CA360
 - Forged elbows and tees: brass CA377
 - O-ring: nitrile rubber
- Suitable for use up to the maximum working pressure of the plastic tubing used; also suitable for vacuum service
- Pre-applied thread sealant (Loctite 516®) on all male pipe threads
- Compatible tubing: SAE J844

Specifications

- Temperature range: -40°F to 212°F (-40°C to 100°C)
- Meets D.O.T. FMVSS 571.106 and SAE J1131, SAE J2494-1, and SAE J2494-3

Male Connectors



| Tube O.D. | Male NPTF | Part # | Pkg Qty |
|-----------|-----------|------------|---------|
| 1/4" | 1/8" | AQ68DOT4X2 | 10 |
| | 1/4" | AQ68DOT4X4 | 10 |
| | 3/8" | AQ68DOT4X6 | 5 |
| 3/8" | 1/4" | AQ68DOT6X4 | 10 |
| | 3/8" | AQ68DOT6X6 | 10 |

Union Connectors



| Tube O.D. | Part # | Pkg Qty |
|-----------|----------|---------|
| 1/4" | AQ62DOT4 | 10 |
| 3/8" | AQ62DOT6 | 10 |

Male Elbows



| Tube O.D. | Male NPTF | Part # | Pkg Qty |
|-----------|-----------|------------|---------|
| 1/4" | 1/8" | AQ69DOT4X2 | 10 |
| | 1/4" | AQ69DOT4X4 | 10 |
| 3/8" | 1/4" | AQ69DOT6X4 | 10 |

D.O.T. Push-In Male Swivel Elbows



| Tube O.D. | Male NPTF | Part # | Pkg Qty |
|-----------|-----------|-------------|---------|
| 1/4" | 1/8" | AQ69DOTS4X2 | 10 |
| | 1/4" | AQ69DOTS4X4 | 10 |
| | 3/8" | AQ69DOTS4X6 | 10 |
| 3/8" | 1/4" | AQ69DOTS6X4 | 10 |
| | 3/8" | AQ69DOTS6X6 | 5 |

E