Venting EZ Boss-Lock Cam & Groove

Application

· Transfer of fluids and solids, with a safe disconnection

Sizes

• 2", 3", and 4"

Features

- · In the event of an accidental disconnection under pressure, the venting feature retains the coupling and allows the stored pressure to vent off
- Povides a venting feature when used with standard cam adapters
- The safety venting feature of this coupling doesn't require a special adapter to work as a system

Materials

- 316 stainless steel
- 356T6 aluminum



Type B Coupler Coupler x Male NPT

Size	Aluminum Part #	316 Stainless Steel Part #
2"	ALBEZ200	RLBEZ200
3"	ALBEZ300	RLBEZ300
4"	ALBEZ400	RLBEZ400

Type C Coupler Coupler x Hose Shank

Size	Aluminum Part #	316 Stainless Steel Part #
2"	ALCEZ200 ¹	RLCEZ200 ¹
3"	ALCEZ300 ¹	RLCEZ300 ¹
4"	ALCEZ400 ¹	RLCEZ400 ¹

¹ Hose drop shank

Type D Coupler Coupler x Female NPT

Te	Size	Aluminum Part #	316 Stainless Steel Part #
	2"	ALDEZ200	RLDEZ200
	3"	ALDEZ300	RLDEZ300
	4"	ALDEZ400	RLDEZ400

Type H **Dust Cap**

5			
20	H	T	5
	1	1	-

Size	Aluminum Part #	316 Stainless Steel Part #
2"	ALHEZ200	RLHEZ200
3"	ALHEZ300	RLHEZ300
4"	ALHEZ400	RLHEZ400

