



WRAPLOCK® & LOX-ON®

Wraplock clamps, with their unique plated carbon steel buckles, conform to many shapes and are suitable for specialized applications.




Wraplock Ideal 59-0




5/16" Hex Head

Plated Carbon Steel



1/2" Band Width

Galvanized Steel




Application torque of 15-20 lbf-in (1.7-2.25 Nm) /
Minimum destructive torque is screw/buckle failure


FIND YOUR PART NUMBER							
Size	Min (in)	Max (in)	Min (mm)	Max (mm)	Band Length (in)	Band Length (mm)	Ideal 59-0
12	1	3-1/2	25	89	12	305	5912
15	1	4-1/2	25	114	15	381	5915
18	1	5	25	127	18	457	5918
24	1	7	25	178	24	610	5924
30	1	9	25	229	30	762	5930
48	1	14-1/2	25	368	48	1219	5948

Product ships flat, shown engaged for illustration purposes only

Lox-On clamps are for extra-tough installations. The unique design provides double-locking security with a 301 stainless steel buckle and high band tension for high sealing pressures.




Lox-On Ideal 69-0




5/16" Hex Head

305 Stainless



1/2" Band Width

300 Stainless - UPC Shield



Maximum installation torque of 20 lbf-in (2.25 Nm) /
Minimum destructive torque is band failure

FIND YOUR PART NUMBER							
Size	Min (in)	Max (in)	Min (mm)	Max (mm)	Band Length (in)	Band Length (mm)	Ideal 69-0
12	11/16	1-1/4	17	32	4-13/16	122	69120
20	11/16	1-3/4	17	44	6-13/32	163	69200
32	11/16	2-5/8	17	67	8-29/32	226	69320
72	1-3/4	5	44	127	16-5/16	414	69720
104	4	7-1/4	102	184	23-5/16	592	69104

Product ships flat, shown engaged for illustration purposes only