## Fuel Delivery / Vapor Recovery

## Single Point Coaxial - Delivery / Vapor Recovery Elbows

## Features & Benefits:

- Available in standard or tall heights to accommodate deep fill boxes
- Rugged modular cast aluminum construction
- Many parts are common throughout the Bayco elbow line, making any necessary maintenance a breeze.
- Grease nipple enables the greasing of the lever stem, and acetal bushings help keep everything moving smoothly, even in the harshest of conditions.
- Bolt on inlets allow the inlet to be changed without having to worry about galling of threaded inlets. See below for replacement inlets (Note: Coaxial inlets are not interchangeable with other Bayco elbow inlets.)
- Ball handle lever enables the operator to easily and positively engage the solid bronze locking arms, onto the underground adapter.
- Top connection is the vapor outlet; lower connection is the fuel delivery inlet.
- Biofuel compatible up to E100 (100% Ethanol) and B20 (20% bio diesel). For detailed fuel compatibility, please refer to the chart shown on page 4.





CA	n	Λ	v
n4	-11	u	^

Part #	Description	"A" Overall Height	"B" Ground Clearance	Fuel Compatibility	
6430	standard height elbow with 3" adapter fuel inlet, 3" adapter vapor outlet	23¾"	11¾"	Gasoline and diesel, up to E100 and B20 biofuels	
6430F	standard height elbow with 3" coupler fuel inlet, 3" adapter vapor outlet	23¾"	11¾"		
6400	standard height elbow with 4" adapter fuel inlet, 3" adapter vapor outlet	23¾"	11¾"		
6400F	standard height elbow with 4" coupler fuel inlet, 3" adapter vapor outlet	23¾"	11¾"		
6400FNPT	standard height elbow with 4" coupler fuel inlet, 3" male npt vapor outlet	23¾"	11¾"		
6430X	tall height elbow with 3" adapter fuel inlet, 3" adapter vapor outlet	26¾"	14¾"		
6430XF	tall height elbow with 3" coupler fuel inlet, 3" adapter vapor outlet	26¾"	14¾"		
6400X	tall height elbow with 4" adapter fuel inlet, 3" adapter vapor outlet	26¾"	14¾"		
6400XF	tall height elbow with 4" coupler fuel inlet, 3" adapter vapor outlet	26¾"	14¾"		
6400XFNPT	tall height elbow with 4" coupler fuel inlet, 3" male npt vapor outlet	26¾"	14¾"		

Elbow options are shown on page 15. See page 89 for repair kits and replacement parts. Biofuel Compatible, see fuel compatibility chart on page 4 for more information.