

Fuel Tanker

Farm and Consumer Nozzles

Features:

- Micro-touch valve provides smooth operation and exceptional flow control
- Pure PTFE stem packing eliminates leaks
- Heavy duty, strong, secure hook makes it easy to hang the nozzle on the pump
- Roto-matic latch pin provides positive auto shut-off
- Smartguard snap-on scuff guard
- With trigger hold-open clip
- Non Underwriters Listed nozzle



gasoline



diesel

Female NPT Inlet	Spout Size	Intended Service	Approximate Flow Rate At 20 PSI (GPM)	Approximate Weight Lbs	Scuff Guard Color	Part #
3/4"	13/16"	Gasoline	18	2½	Black	DN7UOBF
3/4"	15/16"	Diesel	23	2½	Green	DN7LOBF

Big Mouth™ Diesel Nozzle

Features and Benefits:

- *This nozzle is not to be used with gravity flow tanks.*
- Lightweight but strong
- Micro-touch valve provides smooth operation and exceptional flow control
- Roto-matic latch pin provides positive auto shut-off
- Pure PTFE packing eliminates stem leaks
- Super tough nylon hand guard
- Snap-on handle cover makes changing scuff guards easy
- With trigger hold-open clip
- Non Underwriters Listed nozzle



Female NPT Inlet	Spout Size	Intended Service	Approximate Flow Rate At 20 PSI (GPM)	Approximate Weight Lbs	Scuff Guard Color	Part #
1"	1-1/8"	Diesel	27	3	Yellow	DFN100

Fuel Master™ Diesel Nozzles

Features and Benefits:

- High flow capacity
- Micro-touch valve provides smooth operation and exceptional flow control
- Roto-matic latch pin provides positive auto shut-off
- Pure PTFE packing eliminates stem leaks
- Super tough nylon hand guard
- Easy to change 'locknut style' spout assembly
- With trigger hold-open clip
- Non Underwriters Listed nozzle



DFN100HF



DFN100SF

Female NPT Inlet	Spout Size	Intended Service	Approximate Flow Rate At 20 PSI (GPM)	Approximate Weight Lbs	Scuff Guard Color	Part #
1"	1-3/16"	Diesel	35	3½	Green	DFN100HF
1"	1-3/16"	Diesel	45	3½	Green	DFN100SF

DEF Automatic Shutoff Nozzle

Features and Benefits:

- Designed for diesel exhaust fluid, aluminum body double coated inside and out with PTFE baked on at 500°F
- Spout: stainless steel
- Wetted parts: stainless, acetal, PTFE
- Seals are FKM-A



BSPP Inlet	Spout Size	Intended Service	Approximate Flow Rate At 20 PSI (GPM)	Approximate Weight Lbs	Scuff Guard Color	Part #
3/4"	13/16"	Diesel	30	3½	Blue	DEFN075