

FILL-RITE®

Digital Display Meters

For Gasoline / Diesel / Biodiesel / E15 / Kerosene /
Heptanes / Stoddard Solvents / Mineral Spirits

900 Series Digital Meters

Flow 6-40 GPM (23-151 LPM)

+/-1.25% accuracy rating

1" | 1.5" inlet/outlet - NPT or BSPT threads

Memory backup in case of power failure

Field/factory calibration

90° movable electronic head

Powered by 2 AA batteries



Included Accessories | Inlet/Outlet Size

900CD	N	1" inlet/outlet (Pictured below right)
900CD1.5	N	1.5" inlet/outlet
900CDBSPT	B	1" inlet/outlet
900CD1.5BSPT	B	1.5" inlet/outlet
900CDP	N	Intrinsically safe barrier, pulse output 1" inlet/outlet (Pictured below left)
900CDPBSPT	B	Intrinsically safe barrier, pulse output 1" inlet/outlet
900CDP1.5	N	Intrinsically safe barrier, pulse output 1.5" inlet/outlet
900CDP1.5BSPT	B	Intrinsically safe barrier, pulse output 1.5" inlet/outlet
900CDPX	N	Pulse output 1" inlet/outlet (Not for explosive atmospheres)
900CDPX1.5	N	Pulse output 1.5" inlet/outlet (Not for explosive atmospheres)
900CDPXBSP	B	Pulse output 1" inlet/outlet (Not for explosive atmospheres)
900CDPX1.5BSPT	N	Pulse output 1.5" inlet/outlet (Not for explosive atmospheres)



820 Series Nutating Disc Meter

Compatible with Water, Diesel, and Mild Chemicals

Flow 2-20 GPM (8-75 LPM)

+/-0.5% accuracy rating

1" NPT inlet/outlet

Factory/field calibration

Powered by 2 AA batteries

DEF Compatible



820 N Meter only