



ALLCRETE TEXTILE

For use in plaster & grout and shotcrete applications, handling a multitude of materials being pumped to concrete structures, dams, tunnel faces, swimming pools, etc. For use as a flexible connection between pumping equipment and hard piping. Exceeds ASME B30.27-2009. 2:1 WP to burst ratio.

Performance + Specs

Construction Tube

- Chemituf® Synthetic Rubber
- Survivor® Synthetic Rubber

Cover

- SBR (Wrapped Impression)

Reinforcement

- Spiral-Plied High-Strength Fabric
- <

Temperature Range

- -25°F / -32°C ~ 180°F / 82°C

Design Factor

- 2:1

Packaging

- 50' lengths, coiled and polywrapped

Branding Spiral

- Example: Allcrete® Textile Ply Plaster, Grout Concrete ContiTech 2" 1233 PSI / 85 Bar WP Weight filled with concrete (150 lbs/ft³). Exceeds ASME B30.27-2009

Coupling

- Refer to Continental Crimp Manual

Non Stock / Sizes

- For special production run minimum requirements, Contact Customer Service

Branding

ALLCRETE TEXTILE #MAINIMAGE#

Order Codes: 549-638 (Chemituf), 549-802 (Survivor)

Product Numbers

ID (in)	ID (mm)	OD (in)	OD (mm)	Length (ft)	Notes	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
3/4	19.10	1.422	36.10	100	Chemituf	1233	8.50	0.59	0.874	
1	25.40	1.672	42.50	100	Chemituf®	1233	8.5	0.72	1.076	20019934
1-1/4	31.80	1.922	48.80	100	Chemituf®	1233	8.5	0.86	1.276	20019938
1-1/2	38.10	2.312	58.70	100	Chemituf®	1233	8.5	1.24	1.839	20019942
2	50.80	2.812	71.40	100	Chemituf®	1233	8.5	1.56	2.322	20019947
2-1/2	63.50	3.375	85.70	100	Chemituf®	1233	8.5	2.05	3.049	20019960
3	76.20	3.950	100.03	100	Chemituf®	1233	8.5	2.64	3.925	20019965
3-1/2	89.90	4.491	114.10	50	Chemituf®	1233	8.5	3.05	4.534	20019967
4	101.60	4.950	125.70	100	Chemituf®	1233	8.5	3.39	5.052	20019971
5	127.00	6.063	154.00	100	Chemituf®	1233	8.5	4.66	6.940	20164566

