



FLEXWING VERSAFUEL

For use in tank truck and in-plant operation to transfer diesel, biodiesel blends, B-100, ethanol blends, gasoline, oil and petroleum base products up to 60% aromatic content.

Performance + Specs

Construction Tube

- Specially Compounded Nitrile (static dissipating)

Reinforcement

- Spiral-plied synthetic fabric with helix wire

Design Factor

- 4:1

Branding Spiral

- Continental ContiTech Flexwing VersaFuel™ 150 PSI WP

Non Stock / Sizes

- 400' Minimum Order

Cover

- Black synthetic rubber with excellent resistance to biodiesel, ethanol, oil/petroleum products and abrasion.

Temperature Range

- -30°F / -34°C ~ 180°F / 82°C

Packaging

- 100' lengths, coiled and polywrapped.

Coupling

- Refer to the Continental ContiTech Industrial Hose Assembly Manual for crimp specifications.

Downloads

- [Alternative Fuel Compatibility \(Tube & Covers\)](#)

Branding

FLEXWING VERSAFUEL #MAINIMAGE#

Order Codes: 543-422

Product Numbers

ID (in)	ID (mm)	OD (in)	OD (mm)	Length (ft)	Color	Bend Radius (in.)	Bend Radius (mm)	Vacuum HG (in.)	Vacuum HG (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1	25.40	1.50	38.10	100	Black	2.00	50.00	29	737	150	1.03	0.59	0.88	20339606
1-1/4	31.80	1.77	44.80	100	Black	3.00	75.00	29	737	150	1.03	0.74	1.10	20339625
1-1/2	38.10	2.03	51.70	100	Black	4.00	100.00	29	737	150	1.03	0.92	1.37	20339626
2	50.80	2.55	64.90	100	Black	5.00	125.00	29	737	150	1.03	1.21	1.80	20339628
2-1/2	63.50	3.07	77.90	100	Black	6.00	150.00	29	737	150	1.03	1.56	2.32	20339627
3	76.20	3.58	91.00	100	Black	7.00	175.00	29	737	150	1.03	1.94	2.89	20339629
4	101.60	4.60	117.00	100	Black	10.00	200.00	29	737	150	1.03	2.53	3.77	20339650

