



GUNITE (TAN)

For the efficient transfer of sand and cement to the placement mixing gun nozzle. Recommended for all types of gunning applications.

Performance + Specs

Construction Tube

- Tan Pureten™ gum rubber or black Tufsyn® rubber

Cover

- Tan Plioflex® synthetic rubber (wrapped impression)

Reinforcement

- Spiral-plied synthetic fabric

Temperature Range

- -40°F / -40°C ~ 180°F / 82°C

Packaging

- 50' lengths, coiled and polywrapped

Branding Spiral

- Example: ContiTech Gunite 150 Max WP

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Non Stock / Sizes

- For special production run minimum requirements, see Appendix D.

Branding

GUNITE (TAN) #MAINIMAGE#

Order Codes: 549-862 (tan Pureten), 549-863 (black Tufsyn), 549-865 (tan Pureten with anti-static wires)

Product Numbers

ID (in)	ID (mm)	OD (in)	OD (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1-1/4	31.80	2.16	54.90	150	1.03	1.24	1.85	20020272
				150	1.03	1.24	1.85	
1-1/2	38.10	2.43	61.70	150	1.03	1.48	2.2	20020274
1-5/8	41.30	2.58	65.50	150	1.03	1.6	2.38	20020277
1-3/4	44.50	2.7	68.60	150	1.03	1.68	2.5	20020278
2	50.80	2.94	74.70	150	1.03	1.86	2.77	20020279

