



## NUTRIFLEX SUCTION & DISCHARGE

Nutriflex S&D is for both dry food transfer and liquid transfer. Nutriflex™ S&D hose is capable of handling almost every type of dry bulk food material or liquid in gravity flow and vacuum service. Nutriflex conforms to USDA Meat and Poultry, 3-A Sanitary, and FDA Standards and is used for transmission of raw and pasteurized milk and other high water content dairy items.

### Performance + Specs

#### Construction Tube

- Clear Pliovic® (FDA, 3-A, USDA compliant) (NSF-61 approved material)

#### Cover

- Clear Pliovic® (corrugated construction)

#### Reinforcement

- Clear high-density rigid Pliovic® helix

#### Temperature Range

- -15°F / -26°C ~ 158°F / 70°C

#### Packaging

- 100' length, coiled, polywrapped

#### Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

#### Non Stock / Sizes

- For special production run minimum requirements, see Appendix D.

### Branding

Not branded

### NUTRIFLEX SUCTION & DISCHARGE #MAINIMAGE#

Order Codes: 586-417 (white), 586-422 (clear)

#### Product Numbers

ID (in)	ID (mm)	OD (in)	OD (mm)	Bend Radius (in.)	Bend Radius (mm)	Vacuum HG (in.)	Vacuum HG (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1	25.40	1.30	33.00	2	51	29	737	60	0.41	0.23	0.34	20013300
1-1/4	31.80	1.56	39.60	3	76	29	737	50	0.34	0.28	0.42	20013303
1-1/2	38.10	1.88	47.80	4	102	29	737	50	0.34	0.33	0.49	20013306
2	50.80	2.43	61.70	4	102	29	737	40	0.28	0.50	0.74	20013309
2-1/2	63.50	3.05	77.30	5	127	29	737	35	0.24	0.86	1.28	20013311
3	76.20	3.56	90.40	7	178	29	737	35	0.24	1.02	1.52	20013313
4	101.60	4.71	119.60	10	254	29	737	35	0.24	1.64	2.44	20013315
6	152.40	6.74	171.20	30	762	29	737	25	0.17	2.43	3.62	20013345

