



VELOCITY BEVERAGE TRANSFER

Velocity Beverage Transfer is primarily for liquid transfer. For beverage transfer of USDA, FDA and NSF-approved materials. Ideal for applications needing lightweight, flexible PVC hose such as milk processing, wineries and microbreweries, including: filtration, barreling, transfer, pressing, and storage and fermentation tanks. Clear PVC allows for visual confirmation of product flow.

Performance + Specs

Construction Tube

- Clear PVC; FDA, 3-A, USDA compliant, NSF-Cover
61 listed materials
- Clear PVC

Reinforcement

- Polyester Synthetic Yarn; High Density Rigid PVC

Temperature Range

- -13°F / -25°C ~ 158°F / 70°C

Packaging

- Coiled & Poly-Wrapped

Design Factor

- 3:1

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Branding

VELOCITY BEVERAGE TRANSFER

Order Codes: 591-103 (Clear / White)

Product Numbers

ID (in)	ID (mm)	OD (in)	OD (mm)	Length (ft)	Color	Bend Radius (in.)	Bend Radius (mm)	Vacuum HG (in.)	Vacuum HG (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1-1/2	38.10	2.03	51.70	100	Clear / White	2.50	63.50	29	737	110	0.76	0.65	0.97	20806470
2	50.80	2.46	62.50	100	Clear / White	4.00	101.60	29	737	100	0.69	0.71	1.060	20806471
3	76.20	3.71	94.20	100	Clear / White	6.00	152.40	29	737	100	0.69	1.42	2.110	20806472
4	101.60	4.75	120.60	100	Clear / White	7.00	177.80	29	737	75	0.52	1.85	2.75	20810398

VELOCITY BEVERAGE BANDING COIL

Order Codes: 586-595 (White)

Product Numbers

ID (in)	ID (mm)	Length (ft)	Color	Part Number
1-1/2	38.10	3	White	20943772
2	50.80	3	White	20888927
3	76.20	3	White	20888928
4	101.60	3	White	20888929

