

ARCTIC ORTAC® PLUS



Product Specification

Application

Arctic Ortac® Plus is a low-temperature hose for air, water, oil, kerosene, fuel oil and some chemical operations where temperatures fall as low as -65°F (-54°C).

Construction Tube

- Low-Temp; Poly Epichlorohydrin (ECO) ARPM Class A (High Oil Resistance)

Cover

- Low-Temp, Poly Epichlorohydrin (ECO) ARPM Class A (High Oil Resistance)

Reinforcement

- 1 Textile Braid (1/4" to 1/2")
- 1 Textile Braid; Static Wire (3/4" & 1")

Temperature Range

- -65 F / -54 C ~ 180 F / 82 C

Design Factor

- 4:1

Packaging

500' reels, maximum 3 pieces, 50' minimum length

Branding

Continental 9.5mm 3/8" Arctic Ortac® Plus 2.1 MPA/300 PSI. Made In USA

Coupling

Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Non Stock / Sizes

For special production run minimum requirements, Contact Customer Service

ARCTIC ORTAC® PLUS #MAINIMAGE#

Order Codes: 536-275

ID (in)	ID (mm)	OD (in)	OD (mm)	Length (ft)	Color	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1/4	6.40	0.63	15.90	500	Blue	300	2.07	0.16	0.24	20159301
3/8	9.53	0.75	19.10	500	Blue	300	2.07	0.21	0.31	20159302
1/2	12.70	0.91	23.00	500	Blue	300	2.07	0.27	0.40	20159303
3/4	19.10	1.18	29.90	500	Blue	300	2.07	0.39	0.58	20159304
1	25.40	1.50	38.20	500	Blue	300	2.07	0.58	0.86	20146766