

FLEXSTEEL SERVICE STATION AIR

Continental FLEXSTEEL SERVICE STATION AIR 1/4" (6.3 mm) 250 PSI WP MADE IN USA

Product Specification

Application

For tire inflation service from towers, reels, or curb connections.

Construction Tube

- Nitrile synthetic rubber, ARPM class B (medium oil resistance)

Cover

- Red or black Nitrile synthetic rubber, abrasion and oil-resistant, ARPM class B (medium oil resistance)

Reinforcement

- Braided (1) steel wire braid

Temperature Range

- 20 F / -29 C ~ 190 F / 88 C

Packaging

500' reels, maximum 3 pieces, 25' minimum

Branding

Example: ContiTech 1/4" Flexsteel® Service Station Air. Made in USA

Coupling

*(Ready 2 Go logo)
- Coupled assemblies available.

Non Stock / Sizes

For special production run minimum requirements, see Appendix D.

FLEXSTEEL SERVICE STATION AIR #MAINIMAGE#

Order Codes: 539-078 (red), 539-097 (black)

ID (in)	ID (mm)	OD (in)	OD (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1/4	6.40	0.61	15.50	250	1.72	0.18	0.28	20023860
3/8	9.53	0.72	18.30	250	1.72	0.23	0.34	20023865