

BLUE FLOUR



Product Specification

Application

Continental Blue Flour is primarily used for dry food transfer. Tank truck or in-plant service hose is for discharge transfer of abrasive materials and dry foods such as flour, cake mixes, etc.

Construction Tube

- Pureten™ Rubber Meets FDA, USDA & 3-A Sanitary Standard 18-03 Certificate #3737

Cover

- SBR (Wrapped Impression)

Reinforcement

- Spiral-plied Synthetic Fabric with 2 Anti-Static Wires

Temperature Range

- -40 F / -40 C ~ 180 F / 82 C

Design Factor

- 4:1

Packaging

Coiled & Poly-Wrapped

Branding Spiral

Continental Blue Flour Discharge 150 PSI FDA

Coupling

Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Non Stock / Sizes

For special production run minimum requirements, Contact Customer Service

BLUE FLOUR #MAINIMAGE#

Order Codes: 549-503 for 1" to 5", 541-503 for 6"

ID (in)	ID (mm)	OD (in)	OD (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
2	50.80	2.68	68.10	150	1.03	1.39	2.070	20019792
3	76.20	3.69	93.70	150	1.03	2.02	3.010	20019794
4	101.60	4.71	119.60	150	1.03	2.63	3.910	20019795
4-1/2	114.30	5.23	132.88	150	1.03	3.16	4.70	20915015
5	127.00	5.72	145.30	150	1.03	3.27	4.870	20019796
6	152.00	6.73	171.00	150	1.03	4.13	6.15	20155719