

ULTRABRAID® BULL HOSE



Product Specification

Application

Ultrabraid Bull Hose is a heavy duty air hose engineered for severe high pressure industrial applications such as service in mines, quarries and construction jobs. Designed to maintain mild oil resistance and durability in high temperature applications up to 302°F with a working pressure of 600 PSI

Construction Tube

- CPE Synthetic Rubber; ARPM Class B (Medium Oil Resistance)

Cover

- CPE Synthetic Rubber; ARPM Class B (Medium Oil Resistance)

Reinforcement

- Brass Coated High Tensile Steel Wire Braid

Temperature Range

- -40 F / -40 C ~ 302 F / 150 C

Design Factor

- 4:1

Packaging

50' or 100' Cut Lengths, Coiled & Stretch Wrapped in Box

Branding

Continental 2" Ultrabraid HD Bull Hose 600 PSI WP 300°F

Coupling

Contact fitting manufacturer for proper fitting recommendation and coupling procedure

ULTRABRAID® BULL HOSE #MAINIMAGE#

Order Codes: 559-406

ID (in)	ID (mm)	OD (in)	OD (mm)	Length (ft)	Color	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
2	50.80	2.57	65.30	50	Black	600	4.14	1.54	2.290	20936476
2-1/2	64.00	3.15	80.00	50	Black	600	4.14	2.53	3.77	21102499
				100	Black	600	4.14	2.53	3.77	21102498
3	76.20	3.56	90.50	50	Black	600	4.14	2.84	4.23	20937717