

DRINKLINE



Product Specification

Application

Drinkline is primarily for liquid transfer. A quality discharge hose designed specifically for the highly demanding service of transferring non-oily liquid products in wineries and breweries.

Construction Tube

- Chlorobutyl Rubber Meets FDA, USDA & 3-A Sanitary Standard 18-03 Certificate #3737

Cover

- Red EPDM with a white spiral stripe (wrapped impression)

Reinforcement

- Multiple Spiral-plyed synthetic fabric

Temperature Range

- 40 F / -40 C ~ 220 F / 104 C

Design Factor

- 4:1

Packaging

100' length, coiled, poly wrapped

Branding

Continental ContiTech Drinkline® 250 PSI FDA, 3-A, & USDA

Coupling

Refer to the Continental Industrial Hose Assembly Manual for crimp specifications.

Downloads

Click the below Icon to Download further information



DRINKLINE #MAINIMAGE#

Order Codes: 549-380

ID (in)	ID (mm)	OD (in)	OD (mm)	Vacuum HG (in.)	Vacuum HG (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
3/4	19.10	1.319	33.50	20	508	250	1.72	0.45	0.670	20990708
1	25.40	1.598	40.60	20	508	250	1.72	0.62	0.923	20990709
1-1/4	31.80	1.862	47.30	20	508	250	1.72	0.74	1.101	20991440
1-1/2	38.10	2.114	53.70	20	508	250	1.72	0.88	1.310	20991441
2	50.80	2.772	70.40	20	508	250	1.72	1.46	2.173	20991442
2-1/2	63.50	3.346	85.00	20	508	250	1.72	2.01	2.991	20991443
3	76.20	3.846	97.70	20	508	250	1.72	2.34	3.482	20991444
4	101.60	4.846	123.10	20	508	250	1.72	3.03	4.509	20991445