

EXTREMEFLEX FOOD GRADE



Product Specification

Application

Continental ExtremeFlex Food Grade is for both dry food transfer and liquid transfer. A high-tech, flexible corrugated hose with pretzel-like agility and proven performance. Best of all, it's available at a non-corrugated price, making it a great value. With ExtremeFlex, there's even more to appreciate:

- Easier to move in and out of tight spaces and around sharp corners.
- Easier to lift and carry, so there are fewer workplace injuries.
- Easier to connect and disconnect, keeping productivity high. highly demanding service of transferring non-oily liquid products in wineries and breweries.

Construction Tube

- White Chemivic™ synthetic rubber - Meets FDA, USDA & 3-A Sanitary Standard 18-03 Certificate #3737

Cover

- White Chemivic™ corrugated synthetic rubber (wrapped impression) Gray and Red color applicable.

Reinforcement

- Spiral-plied synthetic fabric with galvanized wire

Temperature Range

- -25 F / -32 C ~ 212 F / 100 C

Packaging

Coiled & polywrapped

Branding Spiral

CONTINENTAL EXTREMEFLEX® FOOD GRADE 150 PSI WP

Coupling

Refer to the Continental Industrial Hose Assembly Manual for crimp specifications.

Non Stock / Sizes

400' minimum order

Downloads

Click the below Icon to Download further information



EXTREMEFLEX FOOD GRADE #MAINIMAGE#

Order Codes: 549-462 (white), 549-164 (gray), 549-707 (red)

ID (in)	ID (mm)	OD (in)	OD (mm)	Bend Radius (in.)	Bend Radius (mm)	Vacuum HG (in.)	Vacuum HG (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1	25.40	1.45	36.90	1	25	29	737	150	1.03	0.61	0.91	20607375
1-1/4	31.80	1.65	42.00	1.25	32	29	737	150	1.03	0.64	0.95	20657376
1-1/2	38.10	1.94	49.30	1.5	38	29	737	150	1.03	0.81	1.21	20656565
2	50.80	2.44	62.00	2	51	29	737	150	1.03	1.05	1.56	20478040
2-1/2	63.50	3.056	77.60	2.5	63.5	29	737	150	1.03	1.63	2.430	20478041
3	76.20	3.56	90.50	3	76	29	737	150	1.03	2.07	3.08	20478043
4	101.60	4.59	116.60	4	102	29	737	150	1.03	2.92	4.35	20478044