

PLIOVIC FG



Product Specification

Application

Pliovic FG Transfer is primarily for liquid transfer and is made with FDA, 3-A, USDA compliant and NSF-61 listed tube and cover materials. This is a versatile, lightweight, reinforced tubing recommended for use in the food and beverage, general air, multipurpose, pharmaceutical, cosmetics industries, as well as with computer component manufacturers, textile mills, and air-actuated equipment.

Construction Tube

- Clear Pliovic®

Cover

- Clear Pliovic®

Reinforcement

- Spiral Synthetic Yarn

Temperature Range

- -23 F / -31 C ~ 70 F / 21 C

Packaging

- 1/4"– 5/8" 300' Bagel Pack, one piece
- 3/4" and 1" 200' Bagel Pack, one piece

Branding

Continental Pliovic® FG FDA & 3-A Compliant 3/8" ID (9.5 mm) 250 PSI WP (1.7 MPa) Made in USA

Coupling

Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Non Stock / Sizes

Contact customer service for availability on cut, coiled, and tied hose lengths.

PLIOVIC FG #MAINIMAGE#

Order Codes: 540-337

ID (in)	ID (mm)	OD (in)	OD (mm)	Length (ft)	Color	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1/4	6.40	0.44	11.20	300	Clear	250	1.72	0.05	0.070	20129509
5/16	7.94	0.50	12.70	300	Clear	250	1.72	0.07	0.100	20129600
3/8	9.53	0.59	15.00	300	Clear	250	1.72	0.08	0.120	20129601
1/2	12.70	0.75	19.10	300	Clear	200	1.38	0.12	0.180	20129602
5/8	15.88	0.87	22.10	300	Clear	200	1.38	0.15	0.220	20129603
3/4	19.10	1.02	25.90	300	Clear	150	1.03	0.19	0.280	20337878
1	25.40	1.34	34.00	300	Clear	125	0.86	0.31	0.460	20316305
1-1/4	31.80	1.72	43.60	225	Clear	125	0.86	0.60	0.890	20463346
1-1/2	38.10	1.98	50.20	200	Clear	125	0.86	0.72	1.070	20463340