

TANKER BARGE DISCHARGE



Product Specification

Application

For discharge applications such as the transfer of petroleum-based products between docks and barges.

Construction Tube

- Nitrile Synthetic Rubber for up to 50% Aromatics

Cover

- Black Wingprene® Synthetic Rubber

Reinforcement

- Spiral-plied Synthetic Fabric with Grounding Wires

Temperature Range

- 25 F / -32 C ~ 220 F / 104 C

Design Factor

- 4:1

Packaging

Chloroplast Heavy-Duty Packaging

Branding Spiral

Continental ContiTech Tanker Barge Discharge 200 PSI WP Nitrile

Coupling

Coupled with standard built-in steel nipple/150#RFSSO flanges. Available in other bolt hole patterns, materials and floating flanges on request. Swage nipples are offered up to 10". Hose assembly is electrically continuous unless otherwise specified by customer.

Non Stock / Sizes

Custom lengths available, contact customer service.

TANKER BARGE DISCHARGE #MAINIMAGE#

Order Codes: 541-426 (Nitrile tube)

ID	ID	OD	OD	Length	Color	WP	WP	Weight	Weight	Part Number
(in)	(mm)	(in)	(mm)	(ft)		(PSI)	(MPa)	(lbs/ft)	(kg/m)	
2	50.80	2.71	68.90		Black	200	1.39	1.57	2.33	
3	76.20	3.71	94.30		Black	200	1.38	2.23	3.32	
4	101.60	5.09	129.30	20	Black	200	1.38	4.30	6.400	20045864
6	152.40	7.08	179.80	20	Black	200	1.38	6.18	9.200	20104917
8	203.20	9.08	230.60		Black	200	1.38	8.06	11.990	20136624
10	254.00	11.06	280.90	50	Black	200	1.38	9.93	14.780	20015537
12	304.80	13.28	337.30	16.5	Black	200	1.38	13.91	20.700	20259811