

# VAPOR RECOVERY DOCK



## Product Specification

### Application

For use in the recovery of petroleum vapors during the transfer of petroleum-based products between docks and tankers or barges.

### Construction Tube

- Nitrile Synthetic Rubber for up to 50% Aromatics. Also Available with a Flosyn® Tube for up to 100% Aromatics.

### Cover

- Black Chemivic™ Synthetic Rubber (Corrugated)

### Reinforcement

- Synthetic Fabric Plies Plus Two (2) Wire Helix

### Temperature Range

- 25 F / -32 C ~ 200 F / 93 C

### Design Factor

- 4:1

### Packaging

Chloroplast heavy-duty packaging

### Branding Spiral

Continental ContiTech Vapor Recovery 25 PSI Max WP

### Coupling

Built-in nipples (or swaged fittings up to 10" ID) fitted with 150# flange with extra 5/8" diameter hole located midway between flange bolt hole as per Coast Guard requirements.

### Non Stock / Sizes

Custom lengths available, contact customer service.

## VAPOR RECOVERY DOCK #MAINIMAGE#

Order Codes: 541-090 (Nitrile Tube), 541-643 (Flosyn® Tube)

ID	ID (in)	OD (in)	OD (mm)	Length (ft)	Color	Bend Radius (in.)	Bend Radius (mm)	Vacuum HG (in.)	Vacuum HG (mm)	Notes	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
6	152.40	6.98	177.20		Black	22	559	29	737	Nitrile	25	0.17	7.10	10.60	
6	152.40	6.95	176.40			22	559	29	737	Flosyn	25	0.17	7.29	10.85	20585185
8	203.20	8.96	227.50	50	Black	30	762	29	737	Nitrile	25	0.17	9.01	13.41	20157291
8	203.20	8.93	226.70			30	762	29	737	Flosyn	25	0.17	9.28	13.81	
10	254.00	11.04	280.50	40	Black	40	1016	29	737	Nitrile	25	0.17	13.58	20.20	20323233
10	254.00	11.01	279.70	50		40	1016	29	737	Flosyn	25	0.17	13.91	20.71	20170523
12	304.80	13.07	331.90	30	Black	60	1524	29	737	Nitrile	25	0.17	16.17	24.08	20014974
12	304.80	13.04	331.10			60	1524	29	737	Flosyn	25	0.17	16.58	24.68	