

SOFTWALL WET EXHAUST



Product Specification

Application

For water discharge applications for engines, toilets, scuppers and bilge pumps. Will not pant. Does not meet SAE J2006 R1 Spec.*

Packaging

25' exact lengths, coiled and polywrapped

Construction Tube

- Nitrile Synthetic Rubber ARPM Class A (High Oil Resistance)

Branding Spiral

Continental ContiTech Industrial ORS/Wet Exhaust

Cover

- Chemivic™ Synthetic Rubber (Wrapped Impression)

Coupling

Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Reinforcement

- Spiral-plied Synthetic Fabric

Temperature Range

- 20 F / -29 C ~ 180 F / 82 C

SOFTWALL WET EXHAUST #MAINIMAGE#

Order Codes: 541-154 (6" ID and Below), 543-154 (6" ID and Above)

| ID (in) | ID (mm) | OD (in) | OD (mm) | Length (ft) | Color | WP (PSI) | WP (MPa) | Weight (lbs/ft) | Weight (kg/m) | Part Number |
|---------|---------|---------|---------|-------------|-------|----------|----------|-----------------|---------------|-------------|
| 1/2 | 12.70 | 0.94 | 23.90 | 25 | Black | 250 | 1.72 | 0.29 | 0.430 | 20123258 |
| 3/4 | 19.10 | 1.18 | 30.00 | 25 | Black | 200 | 1.38 | 0.26 | 0.380 | 20126043 |
| 7/8 | 22.23 | 1.30 | 33.20 | 25 | Black | 200 | 1.38 | 0.44 | 0.650 | 20115943 |
| 1 | 25.40 | 1.43 | 36.30 | 25 | Black | 150 | 1.03 | 0.48 | 0.710 | 20107027 |
| 1-1/8 | 28.60 | 1.57 | 39.90 | 25 | Black | 150 | 1.03 | 0.54 | 0.800 | 20156178 |
| 1-1/4 | 31.80 | 1.69 | 43.00 | 25 | Black | 150 | 1.03 | 0.59 | 0.870 | 20113717 |
| 1-5/16 | 33.30 | 1.75 | 44.50 | 25 | Black | 125 | 0.86 | 0.64 | 0.900 | 20107028 |
| 1-3/8 | 34.90 | 1.81 | 46.00 | 25 | Black | 125 | 0.86 | 0.66 | 0.950 | 20110836 |
| 1-1/2 | 38.10 | 1.92 | 49.00 | 25 | Black | 100 | 0.69 | 0.62 | 0.920 | 20107029 |
| 1-5/8 | 41.30 | 2.06 | 52.50 | 25 | Black | 100 | 0.69 | 0.74 | 1.100 | 20107050 |
| 1-3/4 | 44.50 | 2.20 | 56.00 | 25 | Black | 100 | 0.69 | 0.80 | 1.190 | 20108751 |
| 1-7/8 | 47.60 | 2.32 | 59.00 | 25 | Black | 100 | 0.69 | 0.84 | 1.250 | 20115942 |
| 2 | 50.80 | 2.51 | 63.70 | 25 | Black | 75 | 0.52 | 1.04 | 1.540 | 20107025 |
| 2-1/8 | 53.98 | 2.64 | 67.10 | 25 | Black | 75 | 0.52 | 1.10 | 1.630 | 20137213 |
| 2-1/4 | 57.15 | 2.75 | 69.90 | 25 | Black | 75 | 0.52 | 1.15 | 1.710 | 20105483 |
| 2-3/8 | 60.30 | 2.94 | 74.70 | 25 | Black | 75 | 0.52 | 1.35 | 2.010 | 20105484 |
| 2-1/2 | 63.50 | 3.05 | 77.60 | 25 | Black | 75 | 0.52 | 1.41 | 2.100 | 20107080 |
| 2-7/8 | 73.00 | 3.44 | 87.40 | 25 | Black | 75 | 0.52 | 1.60 | 2.310 | 20107081 |
| 3 | 76.20 | 3.54 | 90.10 | 25 | Black | 50 | 0.34 | 1.66 | 2.470 | 20105485 |
| 3-1/8 | 79.40 | 3.70 | 94.00 | 25 | Black | 50 | 0.34 | 1.74 | 2.590 | 20137215 |
| 3-1/2 | 88.90 | 4.09 | 109.00 | 25 | Black | 50 | 0.34 | 1.94 | 2.890 | 20107082 |
| 4 | 101.60 | 4.57 | 116.10 | 25 | Black | 50 | 0.34 | 2.18 | 3.240 | 20110837 |
| 4-1/2 | 114.30 | 5.06 | 128.60 | 25 | Black | 30 | 0.21 | 2.43 | 3.620 | 20110838 |
| 5 | 127.00 | 5.56 | 141.30 | 25 | Black | 30 | 0.21 | 2.68 | 3.990 | 20118697 |
| 5-1/2 | 139.70 | 6.09 | 154.80 | 25 | Black | 30 | 0.21 | 2.94 | 4.380 | 20137217 |
| 6 | 152.40 | 6.56 | 166.60 | 25 | Black | 30 | 0.21 | 3.19 | 4.750 | 20114451 |
| 6-5/8 | 168.30 | 7.37 | 187.30 | 25 | Black | 30 | 0.21 | 4.78 | 7.120 | 20126042 |

