

LPG DELIVERY PRO

LPG Deliver Pro™ is for residential and commercial delivery/transfer of liquid propane gas, LPG dispensing and LPG portable heaters. Excellent cold weather flexibility, a smooth cover for low drag resistance, and a low extraction tube to reduce contamination. The hose meets UL, CGA and DOT requirements. Additional applications require prior approval. Not for LPG appliances or other consumer applications.

Performance + Specs

Construction Tube

• Nitrile Synthetic Rubber

Cover

Synthetic Rubber

Reinforcement

• 4 Textile Spiral Reinforced

Temperature Range

• -40°F / -40°C ~ 180°F / 82°C

Packaging

1 1/4"

400' reels, maximum 3 pieces,

50' increments

1 1/2" 50' increments

300' reels, maximum 3 pieces,

Branding

• 1" (25.4mm) LPG Delivery Pro™ CGA Type 1 LPG-Hose Issue No. E- 8167 350 PSI (2.4 MPa) Max WP. Made in U.S.A.

Coupling

• For STAR Distributors, please refer to LPG Delivery Pro™ crimp specs and use ContiTech approved Male NPT fittings. Premade Factory Assemblies also available.

Branding

1" (25.4mm) LPG Delivery Pro™ CGA Type 1 LPG-Hose Issue No. E- 8167 350 PSI (2.4 MPa) Max WP. Made in U.S.A.

LPG DELIVERY PRO #MAINIMAGE#

Order Codes: 595-042

Product Numbers								
ID (in)	ID (mm)	OD (in)	OD (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1/2	12.70	0.93	23.60	350	2.41	0.25	0.37	20640184
3/4	19.10	1.23	31.20	350	2.41	0.38	0.57	20640185
1	25.40	1.49	37.80	350	2.41	0.51	0.76	20889288
1-1/4	31.80	1.80	45.60	350	2.41	0.67	1.00	20942586
1-1/2	38.10	2.04	51.80	350	2.41	0.78	1.16	20933077

