

LPG DELIVERY PRO CGA TYPE 1 LPG HOSE

LPG DELIVERY PRO PREMADE FACTORY ASSEMBLIES

LPG Delivery Pro™ is for residential and commercial delivery/transfer of liquid propane gas. Excellent cold weather flexibility, a smooth cover for low drag resistance, and a low extraction tube to reduce contamination. The hose meets UL, CGA and DOT requirements – the only UL-Listed LPG bobtail transfer assembly available in the market. Hoses are approved for use in LPG bobtail delivery, LPG dispensing, and LPG industrial portable heater applications only. Additional applications require prior approval. Not for LPG appliances or other consumer applications.

Performance + Specs

Construction Tube

- Nitrile Synthetic Rubber

Cover

- Synthetic Rubber

Reinforcement

- 4 Textile Spiral Reinforced

Temperature Range

- -40°F / -40°C ~ 180°F / 82°C

Design Factor

- 4:1

Packaging

- Coupled assemblies, carton packaging with test certificates

Branding

- 1" (25.4mm) LPG Delivery Pro™ CGA Type 1 LPG-Hose Issue No. E-8167 350 PSI (2.4 MPa) Max WP. Made in U.S.A.

Coupling

- Male NPT, Factory Installed Crimped Fittings

Branding

1" (25.4mm) LPG Delivery Pro™ CGA Type 1 LPG-Hose Issue No. E-8167 350 PSI (2.4 MPa) Max WP. Made in U.S.A.

LPG DELIVERY PRO PREMADE FACTORY ASSEMBLIES #MAINIMAGE#

Order Codes: 581-412

Product Numbers

ID (in)	ID (mm)	OD (in)	OD (mm)	Length (ft)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1/2	12.70	0.93	23.60	100	350	2.41	0.25	0.37	20581706
3/4	19.10	1.23	31.20	150	350	2.41	0.38	0.57	20487242
1	25.40	1.49	37.80	150	350	2.41	0.51	0.76	20458416
1-1/4	31.80	1.80	45.60	100	350	2.41	0.67	1.00	20943899
1-1/2	38.10	2.04	51.80	125	350	2.41	0.78	1.16	20796315

