

FLEXSTEEL® FUTURA VAPOR ASSIST

For Stage II Vacuum Assist Systems where a pump in the dispenser pulls the gasoline vapors away from the vehicle fill pipe during fueling. The wire-braid construction for the fuel hose provides excellent kink resistance, low computer creep and long service life. Flexsteel® Futura™ Vapor Assist is UL 330 approved.

Performance + Specs

Construction Tube

- NITRILE SYNTHETIC RUBBER

Cover

- FUTURIN™ SYNTHETIC RUBBER

Reinforcement

- 1 LAYER; BRAIDED; STEEL WIRE

Temperature Range

- -40°F / -40°C ~ 140°F / 60°C

Design Factor

- 5:1

Packaging

- Coupled lengths only, 6 pieces per box

Coupling

- Available as factory coupled assemblies only.

Non Stock / Sizes

- For special production run minimum requirements, contact customer service.

Branding

Continental Flexsteel® Futura™ Vapor Assist 3/4" Made in USA

FLEXSTEEL® FUTURA VAPOR ASSIST #MAINIMAGE#

Order Codes: 532-362

Product Numbers

ID (in)	ID (mm)	OD (in)	OD (mm)	Length (ft)	Coupled Ends	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
3/4	19.10	1.13	28.70	.83	MXM	50	.34	0.45	0.67	20022236
7/8	22.23	1.25	31.80	10	MXMS	50	.34	0.49	0.73	20022290

