



## MIL - DTL - 13444H TYPE I

This hose is designed for fuel and oil lines in military vehicles and other military applications.

### Performance + Specs

Meets or exceeds the performance requirements of:

- MIL-DTL-13444H Type I

**Inner Tube**

NBR (Nitrile Synthetic Rubber) Black

**Reinforcement**

Single-fabric braid

**Cover**

CR (Polychloroprene) Black

**Temperature Range**

-65F to 250F

### Key Features



4:1 Safety Factor



Military Applications Type I

### Branding

Continental MIL-H-13444 I 1/2" 2Q18 OZ 63906

### Product Numbers

SAP	Product #	ID		OD		Max Working Pressure		Bend Radius		MIN BURST Pressure		Fitting Type	Weight (lb/ft)	
		Fraction	in.	mm.	in.	mm.	PSI	MPa	in.	mm.	PSI			Mpa
20472785	MIL-H-13444-I-3	3/16	0.19	4.80	0.44	11.10	425	2.9	2.00	50.80	1700	11.70	UC	0.07
20468052	MIL-H-13444-I-4	1/4	0.25	6.40	0.50	12.70	300	2	2.25	57.15	1250	8.60	UC	0.09
20470472	MIL-H-13444-I-5	5/16	0.31	7.90	0.56	14.30	275	1.9	2.75	69.85	1100	7.60	UC	0.1
20472786	MIL-H-13444-I-6	3/8	0.38	9.50	0.63	15.90	250	1.7	3.00	76.20	1000	6.90	UC	0.11
20485914	MIL-H-13444-I-8	1/2	0.50	12.70	0.78	19.80	200	1.4	3.75	95.25	750	5.20	UC	0.17
20490906	MIL-H-13444-I-10	5/8	0.63	15.90	0.97	25.60	175	1.2	4.75	120.65	700	4.80	UC	0.22
20493008	MIL-H-13444-I-12	3/4	0.75	19.00	1.09	27.80	125	0.9	5.50	139.70	500	3.40	UC	0.26

### Fittings