



PYROFLEX HOT TAR & ASPHALT II

For the transfer of high temperature petroleum-based materials such as tar, asphalt and hot oils. It is suitable for suction and discharge service on tank trucks, tank cars or at bulk stations. Heat resistant tube and Flexten reinforcement. (Hot oils only rated to 200°F)

Performance + Specs

Construction Tube

- Black Nitrile (Special Heat Resistant) Synthetic Rubber ARPM Class A (High Oil Resistance)

Cover

- Black Wingprene® Synthetic Rubber ARPM Class A (High Oil Resistance) with Spiral Red Stripe

Reinforcement

- Spiral-plied Flexten® with Wire Helix

Temperature Range

- 25°F / -32°C ~ 350°F / 177°C

Packaging

- 100' lengths, coiled and polywrapped

Design Factor

- 4:1

Branding Spiral

- Continental ContiTech Pyroflex® Hot Tar & Asphalt II 150 PSI

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Non Stock / Sizes

- For special production run minimum requirements, see Appendix D.

Branding

PYROFLEX HOT TAR & ASPHALT II #MAINIMAGE#

Order Codes: 543-118

Product Numbers

ID (in)	ID (mm)	OD (in)	OD (mm)	Length (ft)	Color	Bend Radius (in.)	Bend Radius (mm)	Vacuum HG (in.)	Vacuum HG (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1-1/2	38.10	2.08	52.80	100	Black	4	102	29	737	150	1.03	1.04	1.550	20017573
2	50.80	2.60	66.00	100	Black	5	127	29	737	150	1.03	1.33	1.980	20017574
2-1/2	63.50	3.09	78.60	100	Black	6	152	29	737	150	1.03	1.67	2.490	20046059
3	76.20	3.65	92.80	100	Black	7	178	29	737	150	1.03	2.23	3.320	20017578
4	101.60	4.68	118.80	100	Black	10	254	29	737	150	1.03	2.91	4.340	20017580