



PYROFLEX HOT TAR WAND

A high quality wand hose used in asphalt crack filling applicator and dispensing service.

Performance + Specs

Construction Tube

- Black Nitrile (Special Heat Resistance)

Reinforcement

- Spiral-plyed (2) Steel Wire

Design Factor

- 4:1

Branding Spiral

- Continental ContiTech Pyroflex® Hot Tar Wand Hose

Non Stock / Sizes

- For special production run minimum requirements, see Appendix D.

Cover

- Black Wingprene® (Wrapped Finish) Flame-Retardant

Temperature Range

- -25°F / -32°C ~ 350°F / 177°C

Packaging

- 100' lengths, coiled and polywrapped

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Branding

PYROFLEX HOT TAR WAND #MAINIMAGE#

Order Codes: 543-632

Product Numbers

ID (in)	ID (mm)	OD (in)	OD (mm)	Length (ft)	Color	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
3/4	19.10	1.33	33.80	100	Black	300	2.07	0.64	0.950	20017982
1	25.40	1.61	40.90	100	Black	300	2.07	0.84	1.250	20017987
1-1/2	38.10	2.11	53.10	100	Black	300	2.07	1.15	1.710	20156594

