



PGC PLACEMENT TEXTILE

An economical version of our Allcrete® Textile hose. For use in plaster & grout and shotcrete applications, handling a multitude of materials being pumped to concrete structures, dams, tunnel faces, swimming pools, etc. Meets ASME B30.27-2009. 2:1 WP to burst ratio.

Performance + Specs

Construction Tube

- Black Chemituf® Synthetic Rubber

Cover

- Black SBR (Wrapped Impression).

Reinforcement

- Spiral-plied High-strength Fabric.

Temperature Range

- -25°F / -32°C ~ 180°F / 82°C

Design Factor

- 2:1

Packaging

- 50' lengths, coiled and polywrapped.

Branding Spiral

- ContiTech PGC Concrete 1,233 PSI / 85 Bar WP

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Non Stock / Sizes

- For special production run minimum requirements, see Appendix D.

Branding

PGC PLACEMENT TEXTILE #MAINIMAGE#

Order Codes: 549-822

Product Numbers

ID (in)	ID (mm)	OD (in)	OD (mm)	Length (ft)	Color	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1	25.40	1.622	41.20	50	Black	1233	8.5	0.64	0.959	20560651
1-1/4	31.80	1.922	48.80	50	Black	1233	8.5	0.86	1.276	20560652
1-1/2	38.10	2.172	55.20	50	Black	1233	8.5	0.99	1.475	20528827
2	50.80	2.691	68.40	50	Black	1233	8.5	1.30	1.932	20528900
2-1/2	63.50	3.254	82.70	50	Black	1233	8.5	1.74	2.582	20528902
3	76.20	3.875	98.40	50	Black	1233	8.5	2.42	3.609	20528904
3-1/2	89.90	4.443	112.90	50	Black	1233	8.5	2.87	4.270	20560653
5	101.60	4.95	125.70	50	Black	1233	8.5	3.39	5.052	

