



## FUEL DISCHARGE

Fuel Discharge hose is for the discharge of gasoline, oil, ethanol blends and other petroleum based products up to 50% aromatic content in tank and industrial applications.

### Performance + Specs

<p><b>Construction Tube</b></p> <ul style="list-style-type: none"> <li>Nitrile Synthetic Rubber ARPM class A (high oil resistance), plus anti-static wires</li> </ul> <p><b>Reinforcement</b></p> <ul style="list-style-type: none"> <li>Spiral-Plied Synthetic fabric; with Static Wire</li> <li>2" to 4" - 2 Ply</li> <li>6" - 4 Ply</li> </ul> <p><b>Design Factor</b></p> <ul style="list-style-type: none"> <li>4:1</li> </ul> <p><b>Branding Spiral</b></p> <ul style="list-style-type: none"> <li>Continental Fuel Discharge</li> </ul> <p><b>Downloads</b></p> <ul style="list-style-type: none"> <li><a href="#">Alternative Fuel Compatibility (Tube &amp; Covers)</a></li> </ul>	<p><b>Cover</b></p> <ul style="list-style-type: none"> <li>(NBR/PVC) CHEMIVIC SYNTHETIC RUBBER; ARPM Class B (Medium Oil Resistance) (543-331)</li> <li>(CR) NEOPRENE SYNTHETIC RUBBER (543-332)</li> </ul> <p><b>Temperature Range</b></p> <ul style="list-style-type: none"> <li>-35°F / -37°C ~ 180°F / 82°C</li> </ul> <p><b>Packaging</b></p> <ul style="list-style-type: none"> <li>100' lengths, coiled and polywrapped</li> </ul> <p><b>Coupling</b></p> <ul style="list-style-type: none"> <li>Refer to the Continental ContiTech Industrial Hose Assembly Manual for crimp specifications</li> </ul>
---	--

### Branding

#### FUEL DISCHARGE #MAINIMAGE#

Order Codes: 543-331 (Black), 543-332 (Red)

Product Numbers										
ID (in)	ID (mm)	OD (in)	OD (mm)	Length (ft)	Color	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
3/4	19.10	1.21	30.70	100	Black	150	1.03	0.42	0.630	20032339
1	25.40	1.46	37.10	100	Black	150	1.03	0.52	0.770	20032357
1-1/4	31.80	1.72	43.70	100	Black	150	1.03	0.63	0.940	20050546
1-1/2	38.10	1.95	49.50		Black	150	1.03	0.73	1.090	20017756
2	50.80	2.49	63.30		Black	150	1.03	0.98	1.460	20017758
2-1/2	63.50	2.98	75.70		Black	150	1.03	1.19	1.770	20032358
3	76.20	3.50	88.90		Black	150	1.03	1.45	2.160	20017764
3-1/2	88.90	4.04	102.60		Black	150	1.03	1.70	2.530	20050547
4	101.60	4.52	114.80		Black	150	1.03	1.91	2.840	20017767
6	152.40	6.63	168.40		Black	150	1.03	3.41	5.070	20126041
8	203.20	8.80	223.60		Black	150	1.03	6.13	9.120	20877643



