



TWIN-LINE GRADE T - TYPE VD

For welding service, compatible with all common welding fuel gases. Meets ARPM IP-7 and CGA E-1 standards for Grade T welding hose. Non-conductive.

Performance + Specs

Construction Tube

- Polychloroprene Synthetic Rubber

Cover

- Chemivac Synthetic Rubber

Reinforcement

- Spiral Synthetic Yarn

Temperature Range

- -40°F / -40°C ~ 120°F / 49°C

Design Factor

- 4:1

Packaging

- 500' reels

Branding

- Continental Twin-Line 1/4" Grade T Fuel Gas Std. Duty Max WP 200 PSI Meets ARPM IP-7/Cga E-1. Made In USA

Coupling

- *(Ready 2 Go logo)
- Coupled assemblies available.

Non Stock / Sizes

- For special production run minimum requirements, Contact Customer Service.

Branding

Continental Twin-Line 1/4" Grade T Fuel Gas Std. Duty Max WP 200 PSI Meets ARPM IP-7/Cga E-1. Made In USA

TWIN-LINE GRADE T - TYPE VD

Order Codes: 569-618

Product Numbers

ID (in)	ID (mm)	OD (in)	OD (mm)	Length (ft)	Color	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
3/16	4.80	0.44	11.20	500	Red/Green	200	1.38	0.13	0.190	20027443
1/4	6.40	0.53	13.50	500	Red/Green	200	1.38	0.18	0.270	20027465
5/16	7.94	0.59	15.00	500	Red/Green	200	1.38	0.22	0.330	20027480
3/8	9.53	0.66	16.80	600	Red/Green	200	1.38	0.26	0.390	20027498

TWIN LINE GRADE T READY 2 GO



Order Codes: 569-618

Product Numbers

ID (in)	ID (mm)	OD (in)	OD (mm)	Length (ft)	Color	Notes	WP (PSI)	WP (MPa)	Part Number
1/4	6.40	0.53	13.50	50	Red / Green	BB Style Fittings	200	1.38	20027453
				100	Red / Green	BB Style Fittings	200	1.38	20027454
3/8	9.53	0.66	16.80	25	Red / Green	BB Style Fittings	200	1.38	20027493
				50	Red / Green	BB Style Fittings	200	1.38	20027495
				100	Red / Green	BB Style Fittings	200	1.38	20027497

