500# Single Jacket All Polyester Fire Hose

Other threads and configurations are available; contact Dixon®

Materials

- Outer construction: single jacket, all polyester
- · Tube construction: EPDM rubber lining

Specifications

- Proof pressure: 500 PSI
- Service test pressure: 250 PSI at ambient temperature 70°F (21°C)
- Working pressure: 225 PSI at ambient temperature 70°F (21°C)

Uncoupled



-				
Size	Bowl	Length	Part #	
1"	1-1/4"	50'	A510-50UC	
		100'	A510-100UC	
1-1/2"	1-3/4"	50'	A515-50UC	
		100'	A515-100UC	
2-1/2"	0.10/16!	50'	A525-50UC	
	2-13/16"	100'	A525-100UC	

Coupled with female and male expansion ring couplings



Size	Length	Rocker Lug Aluminum NST (NH) Part #	Rocker Lug Brass NST (NH) Part #	Rocker Lug Aluminum NPSH Part #
- "	50'	A510-50RAF		A510-50RAS
1"	100'	A510100RAF		A510100RAS
1.1.0	25'	A515-25RAF		A515-25RAS
	50'	A515-50RAF	A515-50RBF	A515-50RAS
1-1/2"	75'	A515-75RAF		A515-75RAS
	100'	A515100RAF	A515100RBF	A515100RAS
2-1/2"	25'	A525-25RAF		A525-25RAS
	50'	A525-50RAF	A525-50RBF	A525-50RAS
	75'	A525-75RAF		
	100'	A525100RAF	A525100RBF	A525100RAS

500# Single Jacket Fire Hose - UL labeled

Coupled with female and male expansion ring couplings

· Impregnated hose and other length threads and configurations are available; contact Dixon

Materials

- · Outer construction: single jacket, all polyester
- · Tube construction: EPDM rubber lining

Specifications

- · Proof pressure: 500 PSI
- Service test pressure: 250 PSI at ambient temperature 70°F (21°C)
- Working pressure: 225 PSI at ambient temperature 70°F (21°C)

Approval

· Underwriters Listed

Size	Coupling Type	Length	NST Thread Part #
1-1/2"	aamba lug braaa	EO'	A515U50CBF
2-1/2"	combo lug, brass	50'	A525U50CBF







500# Single Jacket Fire Hose - Color Impregnated

Feature

· Consult Dixon® for pricing and availability of other colors, lengths, threads, and configurations . Service test pressure: 250 PSI

- · Outer construction: single jacket, all polyester
- Tube construction: EPDM rubber lining

Specifications

- Proof pressure: 500 PSI
- Working pressure: 225 PSI at ambient temperature 70°F (21°C)



orange



red

Coupled with female and male expansion ring couplings

Size	Coupling Type	Length	Color	Part #
	rocker lug, aluminum, NST (NH)		yellow	A515Y50RAF
	rocker lug, aluminum, NPSH			A515Y50RAS
	rocker lug, aluminum, NST (NH)	50'	red	A515R50RAF
	rocker lug, aluminum, NPSH	50		A515R50RAS
	rocker lug, aluminum, NST (NH)		orange	A5150R50RAF
	rocker lug, aluminum, NPSH			A5150R50RAS

800# Double Jacket All Polyester Fire Hose

Feature

· Consult Dixon for pricing and availability of 75' lengths and other threads and configurations

Materials

- · Outer construction: double jacket, all polyester
- Tube construction: EPDM rubber lining

Specifications

- Proof pressure: 800 PSI
- · Service test pressure: 400 PSI
- · Working pressure: 360 PSI at ambient temperature 70°F (21°C)



Coupled with female and male expansion ring couplings

Size	Length	Rocker Lug Aluminum NST (NH) RAF Part #	Rocker Lug Brass NST (NH) RBF Part #	Rocker Lug Aluminum NPSH RAS Part #
1-1/2"	25'	D815-25RAF		
	50'	D815-50RAF	D815-50RBF	D815-50RAS
	100'	D815100RAF	D815100RBF	D815100RAS
2-1/2"	25'	D825-25RAF		
	50'	D825-50RAF	D825-50RBF	D825-50RAS
	100'	D825100RAF	D825100RBF	D825100RAS

800# Double Jacket Fire Hose - Color Impregnated

Feature

· Other lengths, threads, couplings, and colors (yellow, red, blue, tan, orange, green, black) are available; contact Dixon

Specifications

- Proof pressure: 800 PSI at 70°F (21°C)
- Service test pressure: 400 PSI at 70°F (21°C)
- Working pressure: 360 PSI at 70°F (21°C)

Materials

- · Outer construction: double jacket, all polyester
- · Tube construction: black, synthetic rubber liner

Coupled with female and male expansion ring couplings

Size	Thread NH (NST)	Coupling Type	Length	Part #
1-1/2" 1-1/2"		rocker lug, aluminum NST (NH)	50'	D815Y50RAF
		rocker lug, aluminum NST (NH)	100'	D815Y100RAF
	1-1/2"	rocker lug, aluminum NPSH	50'	D815Y50RAS
		rocker lug, aluminum NPSH	100'	D815Y100RAS
1-3/4"		rocker lug, aluminum NST (NH)	50'	D817Y50RAF
2-1/2" 2-1/2"	rocker lug, aluminum NST (NH)	50'	D825Y50RAF	
	2-1/2"	rocker lug, aluminum NST (NH)	100'	D825Y100RAF
3"		rocker lug, aluminum NST (NH)	50'	D8325Y50RAF

