

## White



Size Range (In) ..... 1.5" to 16"  
 ..... custom to 24"  
 Standard Length (Ft) ..... 25'  
 Standard Color ..... white  
 Temperature Range (°F) ..... -20° to 325°

- Double-ply acrylic coated polyester fabric hose reinforced with a spring steel wire helix
- Efficient flow characteristics
- Designed for applications with wide temperature ranges
- Good abrasion resistance
- Ideal for clean room applications
- Manufactured with FDA acceptable materials



## FSP-1



Size Range (In) ..... 3" to 12"  
 Standard Length (Ft) ..... 25'  
 Standard Color ..... black with orange wearstrip  
 Temperature Range (°F) ..... -20° to 180°

- Single-ply PVC vinyl coated polyester fabric hose reinforced with a spring steel wire helix and external PVC wearstrip
- Wearstrip offers additional external abrasion and drag resistance
- Low friction loss
- Great chemical and moisture resistance
- Listed as UL 94V-0 flame retardant
- Other wearstrip colors available
- Available without a wearstrip for a more economical option
- Available in metric sizes, consult sales team on pricing and minimums



## FSP-2



Size Range (In) ..... 3" to 12"  
 Standard Length (Ft) ..... 25'  
 Standard Color ..... black with orange wearstrip  
 Temperature Range (°F) ..... -20° to 180°

- Double-ply PVC vinyl coated polyester fabric hose reinforced with a spring steel wire helix and external PVC wearstrip
- Wearstrip offers additional external abrasion and drag resistance
- Great moisture, mildew and chemical resistance
- Low friction loss
- Listed as UL 94V-0 flame retardant
- Other wearstrip colors available
- Available in a heavy duty bridge construction in sizes 12" to 24" (FSP Bridge)



## Accessories

### Flexaust® End Finishes

Also available for our Heat-Flex® (excluding Reduced Cuff and Felt Flange) and Springflex® hoses.



Enlarged Cuff



Steel Flange



Fabric Cuff



Reduced Cuff



Felt Flange

