

## FSP-5




Size Range (In) ..... 4" to 24"  
 ..... custom to 48"  
 Standard Length (Ft) ..... 25'  
 Standard Color ..... yellow with black wearstrip  
 Temperature Range (°F) ..... -20° to 180°

- Single-ply PVC vinyl coated polyester fabric hose reinforced with a spring steel wire helix and external PVC wearstrip
- Lightweight duct for blower applications
- Great compressibility with an 11:1 compressibility ratio
- Retractability allows for convenient storage and easy transport in a fraction of its fully extended length
- Wearstrip offers additional external abrasion and drag resistance
- PVC material resists ozone, UV rays and moisture
- Listed as UL 94V-0 flame retardant
- Manufactured with materials that meet NFPA 701 standards
- Available in static conductive version (FSP-5 SC)
- Shown with optional cuff



## SD-W



Size Range (In) ..... 4" to 24"  
 ..... custom to 60"  
 Standard Length (Ft) ..... 25'  
 Standard Color ..... yellow with black wearstrip  
 Temperature Range (°F) ..... -65° to 250°

- Single-ply neoprene coated polyester fabric hose reinforced with a spring steel wire helix and external PVC wearstrip
- Ideal for moving large volumes of air in portable or permanent ventilation/exhaust systems
- Wearstrip offers additional external abrasion and drag resistance
- Great compressibility
- Retractability allows for convenient storage and easy transport in a fraction of its fully extended length
- Listed as UL 94V-0 flame retardant
- Available in a self-retracting version (STO), 4" to 8" only
- Shown with optional cuff



## SD



Size Range (In) ..... 4" to 24"  
 ..... custom to 60"  
 Standard Length (Ft) ..... 25'  
 Standard Color ..... yellow  
 Temperature Range (°F) ..... -65° to 250°

- Single-ply neoprene coated polyester fabric hose reinforced with a spring steel wire helix
- Ideal for moving large volumes of air in portable or permanent ventilation/exhaust systems
- Great compressibility
- Retractability allows for convenient storage and easy transport in a fraction of its fully extended length
- Listed as UL 94V-0 flame retardant
- Shown with optional cuff



## Accessories

### Springflex® End Finishes

Flexaust® offers a variety of end finishes including several types of fabric cuffs for the Springflex® product line. Assembling hoses with various types of required end finishes is another way in which Flexaust® services its customers and reduces costs.



Sewn Cuff



Standard/Enclosed Belted Cuff

