

Flex-Lok® 550



Size Range (In) 4" to 18"
 custom to 20"
 Standard Length (Ft) 25'
 Standard Color silver
 Temperature Range (°F) -65° to 550°

- Single-ply silicone coated fiberglass fabric hose mechanically crimped in a continuous process
- Fabric is locked around a coated steel wire by a metal strip formed into a clip
- Metal strip acts as a wearstrip and offers outstanding external abrasion resistance
- Extremely flexible and compressible
- Manufactured with flame retardant materials
- Ideal for medium temperature heater and floor exhaust applications
- Available with a non-marking TPR rubber clip cover to protect the helix and the equipment that is attached to the hose



F



Flex-Lok® 600



Size Range (In) 4" to 12"
 custom to 20"
 Standard Length (Ft) 25'
 Standard Color silver
 Temperature Range (°F) -65° to 600°

- Double-ply construction silicone coated fiberglass fabric hose with a heat-resistant fiberglass liner mechanically crimped in a continuous process
- Fabric is locked around a coated steel wire by a metal strip formed into a clip
- Metal strip acts as a wearstrip and offers outstanding external abrasion resistance
- Extremely flexible and compressible
- Manufactured with flame retardant materials
- Ideal for medium temperature fume control and vehicle exhaust applications
- Available with a non-marking TPR clip cover to protect the helix and the equipment that is attached to the hose



F

Flex-Lok® 1050



Size Range (In) 4" to 18"
 custom to 20"
 Standard Length (Ft) 25'
 Standard Color silver with a silver liner
 Temperature Range (°F) -65° to 1050°

- Double-ply construction aluminum coated fiberglass fabric hose with a heat-resistant fiberglass liner mechanically crimped in a continuous process
- Fabric is locked around a coated steel wire by a metal strip formed into a clip
- Metal strip acts as a wearstrip and offers outstanding external abrasion resistance
- Extremely flexible and compressible with good flex characteristics
- Fiberglass liner increases tensile strength for a longer life cycle
- Ideal for engine and dynamometer testing, reel, drop systems and paper mill drying applications



F

Flex-Lok® TCF



Size Range (In) 4" to 12"
 custom to 20"
 Standard Length (Ft) 25'
 Standard Color black with a silver liner
 Temperature Range (°F) -60° to 600°

- Double-ply construction Teflon® fabric hose with a heat-resistant fiberglass liner mechanically crimped in a continuous process
- Fabric is locked around a coated steel wire by a metal strip formed into a clip
- Metal strip acts as a wearstrip and offers outstanding external abrasion resistance
- Excellent fatigue resistance and good flex characteristics
- Sealed exterior prevents the escape of dangerous fumes
- Ideal for reel, drop systems and venting many of today's harsh chemicals
- Available with a non-marking TPR clip cover to protect the helix and the equipment that is attached to the hose



F

