

4502 BLUE PVC WATER DISCHARGE BULK HOSE & ASSEMBLIES



CONSTRUCTION: Tube and cover are blue PVC. Reinforcement is knitted polyester yarn.

TEMPERATURE: -14°F (-26°C) to +150°F (+66°C)

BRANDING: Jason logo WP XX (PSI) ID.

APPLICATION: For general purpose water discharge in construction, agriculture and drip irrigation.

DESIGN FACTOR: 3:1

FEATURES:

- Light and easy to handle
- Rolls flat for convenient storage
- Homogeneous construction eliminates tube & cover separation
- Maximum bonding as tube & cover are extruded simultaneously

BULK HOSE

Part Number	I.D.		Wall Thickness		Reinf.	Max W.P. @ 68°F		Vacuum @ 68°F	Weight		Std. Length (ft.)
	in.	mm	in.	mm		PSI	BAR		lb./ft.	KG/m	
4502-1000	1	25.40	0.056	1.42	Knitted	85	5.86	n/a	0.10	0.15	300
4502-1500	1-1/2	38.10	0.056	1.42	Knitted	85	5.86	n/a	0.21	0.31	300
4502-1500-050	1-1/2	38.10	0.056	1.42	Knitted	85	5.86	n/a	0.21	0.31	50
4502-2000	2	50.80	0.056	1.42	Knitted	85	5.86	n/a	0.25	0.37	300
4502-2000-050	2	50.80	0.056	1.42	Knitted	85	5.86	n/a	0.25	0.37	50
4502-2500	2-1/2	63.50	0.060	1.52	Knitted	75	5.17	n/a	0.29	0.43	300
4502-3000	3	76.20	0.062	1.57	Knitted	70	4.83	n/a	0.39	0.58	300
4502-3000-050	3	76.20	0.062	1.57	Knitted	70	4.83	n/a	0.39	0.58	50
4502-4000	4	101.60	0.062	1.57	Knitted	70	4.83	n/a	0.60	0.89	300
4502-6000	6	152.40	0.077	1.96	Knitted	50	3.45	n/a	1.15	1.71	300
4502-8000	8	203.20	0.089	2.26	Knitted	45	3.10	n/a	1.20	1.79	300

HOSE ASSEMBLIES - CUT • COUPLED • COILED • TIED

Part Number	I.D.		Length (ft.)	Coupling	Reinf.	Max W.P. @ 68°F		Weight	
	in.	mm				PSI	BAR	lb.	KG
4502-1500-050AB	1-1/2	38.10	50	1-1/2" I.D. AB Pin Lug (M x F)	Knitted	85	5.86	9.00	4.08
4502-2000-050AB	2	50.80	50	2" I.D. AB Pin Lug (M x F)	Knitted	85	5.86	12.00	5.44
4502-3000-050AB	3	76.20	50	3" I.D. AB Pin Lug (M x F)	Knitted	70	4.83	22.00	9.98
4502-1500-050CE	1-1/2	38.10	50	1-1/2" I.D. Aluminum Cam Lock (C x E)	Knitted	85	5.86	9.00	4.08
4502-2000-050CE	2	50.80	50	2" I.D. Aluminum Cam Lock (C x E)	Knitted	85	5.86	12.00	5.44
4502-3000-050CE	3	76.20	50	3" I.D. Aluminum Cam Lock (C x E)	Knitted	70	4.83	22.00	9.98
4502-4000-050CE	4	101.60	50	4" I.D. Aluminum Cam Lock (C x E)	Knitted	70	4.83	32.00	14.52
4502-6000-050CE	6	152.40	50	6" I.D. Aluminum Cam Lock (C x E)	Knitted	50	3.45	52.00	23.59

Working pressure (W.P.) is temperature dependent. See the General Information section Table II - Pressure Re-Rating for increased Temperatures (Page 11) for more information.

All sizes may not be stocked in all locations. Check with customer service for availability.

We disclaim any liability for use of our products in applications other than which they are designed.

WARNING: This product can expose you to chemicals including DINP, which is known to the State of California to cause cancer, birth defects or other reproductive harm. For more information visit www.P65WARNINGS.ca.gov