WATER HOSE



4615

CLEAR/WHITE HELIX PVC WATER SUCTION HOSE







CONSTRUCTION: Tube is PVC, smooth, clear. Cover

is also PVC, smooth to lightly corrugated. Reinforcement is a

PVC helix.

TEMPERATURE: -14°F (-26°C) to +150°F (+66°C)

BRANDING: None.

DESIGN FACTOR: 3:1

APPLICATION: Suction, discharge or gravity flow of

water, salt water and oily water in construction, agriculture, mining or

equipment rental.

FEATURES:

- Cover is weather, ozone and UV resistant
- Lightweight and flexible
- Allows for visual flow inspection

Part Number	I.D.		O.D.		Reinf.	Max W.P. @ 68°F		Vacuum	Weight		Minimum Bend Radius		Std. Length
	inch	mm	inch	mm		PSI	BAR	@ 68°F	lb./ft.	KG/m	inch	mm	(ft.)
4615-0750	3/4	19.05	0.95	24.13	PVC Helix	100	6.89	28.0	0.16	0.24	2.00	50.80	100
4615-1000	1	25.40	1.22	30.99	PVC Helix	100	6.89	28.0	0.20	0.30	5.00	127.00	100
4615-1250	1-1/4	31.75	1.41	35.81	PVC Helix	100	6.89	28.0	0.26	0.39	6.00	152.40	100
4615-1500	1-1/2	38.10	1.77	44.96	PVC Helix	100	6.89	28.0	0.35	0.52	7.00	177.80	100
4615-2000	2	50.80	2.32	58.93	PVC Helix	100	6.89	28.0	0.54	0.80	9.00	228.60	100
4615-2500	2-1/2	63.50	2.87	72.90	PVC Helix	80	5.52	26.0	0.70	1.04	11.00	279.40	100
4615-3000	3	76.20	3.35	85.09	PVC Helix	75	5.17	26.0	0.93	1.38	14.00	355.60	100
4615-4000	4	101.60	4.49	114.05	PVC Helix	60	4.14	26.0	1.48	2.20	18.00	457.20	100
4615-6050	6	152.50	6.46	164.08	PVC Helix	50	3.45	26.0	2.89	4.30	31.00	787.40	50

Working pressure (W.P.) is temperature dependent. See the General Information section Table II - Pressure Re-Rating for increased Temperatures (Page 11) for more information.