WATER HOSE



4703 HEAVY DUTY DJ MILL DISCHARGE HOSE & ASSEMBLIES







CONSTRUCTION: Tube is SBR, smooth and black.

The cover is a double jacket made

with 100% polyester.

TEMPERATURE: -25°F (-32°C) to +185°F (+85°C)

BRANDING: Service Pressure 300 PSI.

APPLICATION: Municipal washdown or hydrant-to-truck

water supply line. Heavy duty equipment/pump rental, ship/deck washdown.

FEATURES:

- Double cover gives heavy duty abrasion resistance
- Rolls flat for easy storage
- · Economical, lightweight and flexible
- Double cover increases service pressure rating

BULK HOSE

Part Number	I.D.		Coupling Bowl		Reinf.	Service Pressure		Test Pressure		Vacuum	Weight		Std. Length
	in.	mm	in.	mm	Plies	PSI	BAR	PSI	BAR	@ 68°F	lb./ft.	KG/m	(ft.)
4703-1500	1-1/2	38.10	1.94	46.04	n/a	300	20.68	600	41.36	600	0.26	0.39	50
4703-2000	2	50.80	2.50	58.74	n/a	300	20.68	600	41.36	600	0.33	0.49	50
4703-2500	2-1/2	63.50	2.81	71.44	n/a	300	20.68	600	41.36	600	0.45	0.67	50
4703-1501	1-1/2	38.10	1.94	46.04	n/a	300	20.68	600	41.36	600	0.26	0.39	100
4703-2001	2	50.80	2.50	58.74	n/a	300	20.68	600	41.36	600	0.33	0.49	100
4703-2501	2-1/2	63.50	2.81	71.44	n/a	300	20.68	600	41.36	600	0.45	0.67	100

HOSE ASSEMBLIES CUT • COUPLED • COILED • TIED

Part	1.1	D .	Reinf.	Thread	Weight		Std. Length	
Number	in.	mm	Plies	Туре	lb.	KG	(ft.)	
4703-1500-050ERNPS	1-1/2	38.10	n/a	NPS	15.00	6.80	50	
4703-1500-050ERNST	1-1/2	38.10	n/a	NST	15.00	6.80	50	
4703-2000-050ERNPS	2	50.80	n/a	NPS	20.00	9.07	50	
4703-2500-050ERNPS	2-1/2	63.50	n/a	NPS	25.00	11.34	50	
4703-2500-050ERNST	2-1/2	63.50	n/a	NST	25.00	11.34	50	

Couplings are
internally expanded,
aluminum, hardcoated
NPS or NST Male x
Female rocker lug

Note: Assembly is rated at 150 PSI. Service pressure is temperature dependent. See the General Information section Table II - Pressure Re-Rating for Increased Temperatures (Page 11) for more information.