









SELECTION GUIDE

CATEGORY	PRODUCT	PAGE	GENERAL DESCRIPTION
Suction & Discharge 	Kanalite Flex CL (100CL)	8	General water suction and discharge hose
	Kanaflo U 113UVCLBK	9	All weather suction and discharge hose
	Kanaflo 110CL/110 (110CL/110GR)	10	Heavy-duty water suction and discharge hose
	Kanaflo 112CL/112AG (112CL/112AG)	11	Economical heavy-duty water suction and discharge hose
	Kanaflo 114CL/114GR	12	Light weight water suction and discharge hose
Cold Weather/Flexible 	Kanaline Blue	13	Heavy-duty water suction and discharge hose for applications requiring combined vacuum, higher working pressures, and increased flexibility
	Kanaflo Blue (116 Blue)	14	Heavy-duty water suction and discharge hose
	Kanalite Blue (100 Blue)	15	Low temp general water suction and discharge hose
	Kanalite CW (100CWFLX)	16	Low temp general water suction and discharge hose
	Kanaflo 116CL (116CL)	17	Heavy-duty water suction and discharge hose
	Kanaline CW	18	Heavy-duty water suction and discharge hose for applications requiring combined vacuum, higher working pressures, and increased flexibility
Heavy Duty 	Kanaline SR	19	Water suction and discharge hose for heavy-duty applications requiring combined vacuum and higher working pressures
	KanaChem RS (220RS)	20	All weather suction and discharge hose
	KanaChem 300 (300GR/EPDM)	21	All weather suction and discharge hose
	KanaChem 390 (390SD)	22	All weather suction and discharge hose
	KanaVac Max (Kanapower AT)	23	Heavy-duty abrasion resistant suction and discharge hose
Abrasion Resistance 	KanaVac AR (180AR)	24	Heavy-duty abrasion resistant suction and discharge hose
	KanaVac STAR (180STAR)	25	Heavy-duty abrasion resistant suction and discharge hose
	KanaVac MV (180MV)	26	Abrasion resistant medium-duty suction and discharge hose
	KanaVac Lite (180BL)	27	Lightweight abrasion resistant blower and suction hose
	KanaVac HR (180HR)	28	High temperature abrasion resistant suction hose
	KanaBoom Lite (KB-Lite)	29	Heavy-duty wet & dry material handling hose with static dissipative polyurethane liner
	KanaBoom (STKB)	30	Heavy-duty abrasion resistance hose with copper grounding wire for handling wet or dry materials
	Kanaline UFG (STKLUGF)	31	Heavy-duty food-grade static dissipative PVC and polyurethane construction with copper grounding wire for handling wet or dry materials
	Kanalite U (100UCLR)	32	Medium-duty polyurethane dry material handling hose

	CONSTRUCTION	TEMP RANGE (F°)	WORKING PRESSURE (72°F, P.S.I.)	SIZE
		-60 -40 -20 0 20 40 60 80 100 120 140		
	Flexible PVC, rigid PVC helix, smooth bore, corrugated O.D.	-13 140	30 to 50	1" to 10"
	Flexible PVC blended with polyurethane, rigid PVC helix, smooth bore, smooth O.D.	-13 140	55 to 86	1" to 3"
	Flexible PVC, rigid PVC helix, smooth bore, smooth O.D.	-13 140	28 to 86	3/4" to 8"
	Flexible PVC, rigid PVC helix, smooth bore, smooth O.D.	-13 140	50 to 80	1-1/4" to 4"
	Flexible PVC, rigid PVC helix, smooth bore, smooth O.D.	-13 140	45 to 65	1-1/4" to 4"
	Flexible cold weather PVC, rigid PVC helix, synthetic braiding, smooth bore, corrugated O.D.	-40 140	30 to 75	1-1/2" to 10"
	Flexible PVC, rigid PVC helix, smooth bore, smooth O.D.	-40 140	21 to 70	1" to 8"
	Cold weather PVC, rigid PVC helix, smooth bore, corrugated O.D.	-40 140	20 to 40	1" to 8"
	Cold weather PVC, rigid PVC helix, smooth bore, corrugated O.D.	-22 140	20 to 25	3" to 6"
	Flexible PVC, rigid PVC helix, smooth bore, smooth O.D.	-22 140	21 to 70	1" to 8"
	Flexible cold weather PVC, rigid PVC helix, synthetic braiding, smooth bore, corrugated O.D.	-22 140	50 to 70	2" to 6"
	Flexible PVC, rigid PVC helix, synthetic braiding, smooth bore, corrugated O.D.	-13 140	28 to 110	1-1/2" to 12"
	SBR rubber with carbon black, rigid PVC helix, smooth bore, smooth O.D.	-40 140	23 to 50	1-1/2" to 6"
	EPDM rubber, polyethylene helix, smooth bore, corrugated O.D.	-40 140	23 to 50	1" to 6"
	EPDM rubber, polyethylene helix, synthetic braiding, smooth bore, corrugated O.D.	-40 140	90 to 100	1-1/4" to 3"
	SBR rubber blended with static dissipating carbon black	-30 140	140	4" to 6"
	SBR rubber blended with static carbon black, rigid PVC helix, smooth bore, corrugated O.D.	-40 140	25 to 45	1-1/4" to 12"
	SBR rubber blended with static carbon black, rigid PVC helix, smooth bore, with copper wire, corrugated O.D.	-40 140	10 to 20	2" to 4"
	SBR rubber with carbon black, rigid PVC helix, smooth bore, corrugated O.D.	-40 140	8	5" to 6"
	SBR rubber blended with static carbon black, rigid PVC helix, smooth bore, corrugated O.D.	-40 140	8 to 18	2-1/2" to 8"
	EPDM rubber, polyethylene helix, metal helical wire, smooth bore, corrugated O.D.	-40 220	30	4" to 8"
	Flexible abrasion polyurethane liner, rigid PVC helix, smooth bore, PVC corrugated O.D. with static dissipating materials.	-40 140	20 to 35	1-1/2" to 8"
	Flexible high abrasion polyurethane liner, rigid PVC helix, synthetic braiding, no direction required, smooth bore, extra UV inhabitant PVC corrugated O.D. with static dissipating materials and copper grounding wire.	-33 140	60 to 75	4" to 8"
	Flexible static dissipative polyurethane liner and PVC, rigid PVC helix, synthetic braiding, no direction required, smooth bore, PVC corrugated O.D. with copper grounding wire.	-33 140	70 to 75	4" to 6"
	Flexible polyurethane lined PVC tube, rigid PVC helix, smooth bore, PVC corrugated O.D.	-13 140	30 to 40	2" to 6"

SELECTION GUIDE

CATEGORY	PRODUCT	PAGE	GENERAL DESCRIPTION
Petroleum 	KanaPower (ST120LT)	33	Tank truck drop hose with static grounding wire; 50% lighter than conventional rubber hose
	KanaVapor (ST120VP)	34	Gasoline vapor recovery hose
	KanaVapor Bio (ST120UACVR)	35	The ultimate all purpose tank truck and terminal vapor recovery hose with clear static dissipating tube and static grounding wire
	KanaPower Bio (ST120UAPDH)	36	The ultimate all purpose tank truck drop hose with clear static dissipating tube and static grounding wire
	KanaPower Max (ST120HP)	37	Tank truck drop hose with static grounding wire; 50% lighter than conventional rubber hose
	Kanaline OR	38	Oil resistant PVC heavy-duty suction and discharge hose *** Oil Use Only, NOT for use with gasoline or similar fuels ***
Food Grade 	Kanalite FG (200SFG)	39	Food grade suction and discharge hose
	Kanalite STFG (ST200SFG)	40	Medium-duty, lightweight, hose for pneumatic conveying
	Kanaflo FG (210HFG)	41	Heavy-duty food grade suction and discharge hose
	Kanaflo MK (212MK)	42	Heavy-duty food grade suction and discharge hose
	Kanaline FW	43	Heavy-duty food grade suction and discharge hose
Duct 	KanaDuct 150 (150CL)	44	Lightweight PVC blower and ducting hose
	KanaDuct 620 (620WD)	45	General ducting and blower hose with metal wire helix
	KanaDuct 625 (620WD WS)	46	General ducting and blower hose with metal wire helix and external wear strip
	KanaDuct 630 (630ED)	47	Medium-duty blower and ducting hose
	KanaDuct 660 (660YD)	48	Heavy-duty duct hose with "safety yellow" helix for high visibility
	KanaDuct 150U (150UDH)	49	Polyurethane medium-duty blower and ducting hose
	Kanalite 155 (155GY)	50	Heavy-duty PVC blower and ducting hose
Specialty 	Kanalite PS UVOR (101PSUVOR)	51	Methane gas recovery at landfills, water suction/discharge. Solid wall construction and extra UV inhibitors provide extended life.
	Kanalite PS (101PS)	52	Methane gas recovery at landfills, water suction/discharge
	Kanaflo Spa (Spa Cream)	53	Flexible PVC spa hose
	KanaDuct Poly (Kanaduct)	54	Duct hose, with interlock construction, allows the inside diameter to be changed by twisting the hose, while still holding its shape
Accessories	Banding Sleeve	55	Plastic banding sleeve for use with ST 120 LT hose
	Banding Coil (black or white)	55	Designed to fit and fill the area between the helix
	Duct Clamp	55	
	PowerLock Clamp	55	
	PowerLock Clamp PS	55	

	CONSTRUCTION	TEMP RANGE (F°)	WORKING PRESSURE (72°F, P.S.I.)	SIZE
		-60 -40 -20 0 20 40 60 80 100 120 140		
	Nitrile rubber static dissipating tube, rigid PVC helix, synthetic braiding, smooth bore, static grounding wire, corrugated O.D.	-30 140	65	2" to 4"
	Nitrile rubber, rigid PVC helix, smooth bore, corrugated O.D., static grounding wire	-40 140	10 to 20	2" to 4"
	Lightweight clear static dissipating non-permeable polyurethane with smooth bore, corrugated O.D., rigid PVC helix, static grounding wire	-52 140	7 to 9	2" to 4"
	Non-permeable polyurethane inner and outer tube with synthetic braiding, smooth bore, corrugated O.D., PVC helix for easy drag, clear static dissipating tube and multi-strand copper static wire	-52 140	65	2" to 4"
	Nitrile rubber static dissipating tube, rigid PVC helix, synthetic braiding, smooth bore, static grounding wire, corrugated O.D.	-30 140	150	3" to 4"
	Flexible oil-resistant PVC, rigid PVC helix, synthetic braiding, smooth bore, corrugated O.D.	-13 140	60 to 80	2" to 4"
	Produced entirely of compounds in compliance with FDA and 3-A non toxic specifications, flexible PVC, rigid PVC helix, smooth bore, corrugated O.D.	-13 140	30 to 50	1" to 4"
	Produced entirely of compounds in compliance with FDA and 3-A nontoxic specifications, flexible PVC, rigid PVC helix, multi-strand copper static grounding wire, smooth bore, corrugated O.D.	-13 140	30 to 45	1-1/2" to 4"
	Produced entirely of compounds in compliance with FDA and 3-A nontoxic specifications, flexible PVC, rigid PVC helix, smooth bore, corrugated O.D.	-13 140	55 to 86	3/4" to 4"
	Produced entirely of compounds in compliance with FDA and 3-A nontoxic specifications, flexible PVC, rigid PVC helix, smooth bore, corrugated O.D.	-13 140	62 to 66	1-1/2" to 3"
	Produced entirely of compounds in compliance with FDA and 3-A nontoxic specifications, flexible PVC, rigid PVC helix, synthetic braiding, smooth bore, corrugated O.D.	-13 140	70 to 110	1-1/2" to 6"
	Flexible PVC, rigid PVC helix, smooth bore, corrugated O.D.	-13 140	2 to 6	2-1/2" to 8"
	EPDM rubber, metal wire helix, smooth bore, slightly corrugated O.D.	-40 220	3 to 12	2" to 12"
	EPDM rubber, metal wire helix, wearstrip, smooth bore, corrugated O.D.	-40 220	3 to 12	2-1/2" to 12"
	EPDM rubber, polypropylene helix, smooth bore, corrugated O.D.	-40 158	—	2" to 8"
	EPDM rubber, polypropylene helix, smooth bore, corrugated O.D.	-40 158	3 to 9	4" to 12"
	Flexible clear polyurethane, rigid PVC helix, smooth bore, corrugated O.D.	-20 140	3 to 9	2-1/2" to 8"
	Flexible PVC, rigid PVC helix, smooth bore, corrugated O.D.	-13 140	10 to 20	1-1/2" to 8"
	Flexible PVC, rigid PVC helix, smooth bore, corrugated O.D.	-13 140	30 to 35	2-3/4" to 4-1/2"
	Rigid PVC and helix	-13 140	30 to 35	2-3/4" to 4-1/2"
	Flexible PVC, rigid PVC helix, smooth bore, smooth O.D.	-13 158	60 to 100	1/2" to 2"
	Interlocked polypropylene	-13 180	—	2-1/2" to 12"
	PVC construction, corrugated inside, smooth O.D.	-40 140	—	—
	PVC	—	—	—
	Steel	—	—	—
	Steel	—	—	—
	Steel	—	—	—