



T204AA Series 75 PSI SBR Water S & D Hose

General Applications:

Suction and discharge of water for irrigation and construction.

Construction:

Tube: Black SBR.

Reinforcement: Spiraled high tensile textile cords with flexible steel helix wire.

Cover: Black SBR – ozone and abrasion-resistant.

Working Pressure:

Constant Pressure – 5 Bar (75 PSI)

Service Temperature Range:

-22°F (-30°C) to +176°F (+80°C)

Branding:

ALFAGOMMA– ITALY – T204 (embossed)

Nominal Specifications

| Series Number | ID (in) | ID (mm) | OD (in) | OD (mm) | Max Rec. WP (psi) | Vacuum HG (in) | Min. Bending Radius at 68°F (in) | Standard Length (ft) | Weight (lbs/ft) |
|---------------|---------|---------|---------|---------|-------------------|----------------|----------------------------------|----------------------|-----------------|
| T204AA600 | 6 | 152 | 6.54 | 166 | 75 | 24 | 30 | 20/25/50/100 | 4.13 |
| T204AA800 | 8 | 203 | 8.70 | 221 | 75 | 21 | 40 | 20/25 | 7.06 |

COUPLING SUGGESTIONS

Quick-Acting, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.

★ Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type and pricing.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.