



## T254AA Series 150 PSI SBR Water Discharge Hose

### General Applications:

Water discharge hose for construction and irrigation.

### Construction:

**Tube:** Black SBR.

**Reinforcement:** High tensile textile cords.

**Cover:** Black SBR – abrasion and ozone-resistant.

### Working Pressure:

Constant Pressure – 10 Bar (150 PSI)

### Service Temperature Range:

-22°F (-30°C) to +176°F (+80°C)

## Nominal Specifications

Series Number	ID (in)	ID (mm)	OD (in)	OD (mm)	Max Rec. WP (psi)	Standard Length (ft)	Weight (lbs/ft)
T254AA150	1 1/2	38	1.89	48	150	100	0.66
T254AA200	2	51	2.40	61	150	100	0.87
T254AA300	3	76	3.46	88	150	100	1.54
T254AA400	4	102	4.49	114	150	100	2.08
T254AA600	6	152	6.54	166	150	100	3.13
T254AA800	8	203	8.62	219	150	50/100	4.64

### COUPLING SUGGESTIONS

Quick-Acting, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.

- ★ Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type and pricing.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.