



INDUSTRIAL



SB SANDBLAST 175 PSI HOSE

NRP PART NUMBER	HOSE I.D. (NOMINAL)		HOSE O.D. (NOMINAL)		RATED W.P.		WT. PER FT. (LBS)	BEND RADIUS (MIN) (IN.)
	(IN.)	(MM)	(IN.)	(MM)	(PSI)	BAR		
SB-12	0.75	19	1.33	34	175	12	0.54	7.48
SB-16	1	25	1.57	40	175	12	0.65	9.84
SB-20	1.25	32	1.88	48	175	12	0.89	12.40
SB-24	1.50	38	2.12	54	175	12	1.45	14.96
SB-32	2	51	2.87	73	175	12	2.20	19.68

Tube: Anti-static Synthetic / Natural Rubber Blended

Reinforcement: 2 Plies of Synthetic Cords

Cover: Anti-static Synthetic / Natural Rubber Blended | Abrasion Resistant

Temperature: -4° F to 176° F (-20° C to 80° C)

Application(s): Sand, metal grits & foundry waste

Offered Length(s): 50 foot only

Safety Factor: 3 : 1

Branding: NRP JONES BLASTER SB (SIZE) SANDBLAST 175 PSI

ISO 9001:2015 CERTIFIED QUALITY SYSTEM
API Q1 9TH EDITION CERTIFIED QUALITY MANAGEMENT SYSTEM