

Novaflex 2150 Water Discharge Hose

A lightweight rubber water discharge hose designed for use on portable pumps by contractors and municipalities.

Construction:

Tube: Black synthetic EPDM rubber

Reinforcement: Plies of polyester tire cord

Cover: Smooth black weather and abrasion resistant rubber

Length: 100ft.

Temperature Range: -30° (-35°C) to +180°F (+82°C)



Part No.	I.D.	O.D.	Plies	WP psi	WT LBS/FT
2150BE-01250-00	1¼	1.44	2	150	0.40
2150BE-01500-00	1½	1.69	2	150	0.47
2150BE-02000-00	2	2.19	2	150	0.62
2150BE-02500-00	2½	2.69	2	150	0.76
2150BE-03000-00	3	3.19	2	150	0.91
2150BE-03500-00	3½	3.74	2	150	1.05
2150BE-04000-00	4	4.24	2	150	1.19
2150BE-05000-00	5	5.32	2	150	1.49
2150BE-06000-00	6	6.32	2	75	1.78
2150BE-06625-00	6⅝	6.94	2	75	1.97
2150BE-08000-00	8	8.33	2	75	2.54
2150BE-08625-00	8⅝	8.95	2	75	2.89
2150BE-10000-00	10	10.43	4	75	4.19
2150BE-10750-00	10¾	11.18	4	75	4.51
2150BE-12000-00	12	12.43	4	75	5.02
2150BE-12750-00	12¾	13.18	4	75	5.33

Novaflex 2151 Heavy Duty Hot Water Washdown Hose

Designed to meet the rugged washdown applications in the food processing industry.

Construction:

Tube: White EPDM

Reinforcement: Multiple layers of polyester cord

Cover: White EPDM non marking. Length: 100ft.

Temperature Range: -40° (-40°C) to +212°F (+100°C)

Not rated for steam



Part No.	I.D.	O.D.	Plies	WP psi	WT LBS/Ft
2151WE-00750-00	¾	1.31	4	300	0.44
2151WE-01000-00	1	1.56	4	300	0.54
2151WE-01250-00	1¼	1.81	4	300	0.65

Novaflex 2152 Water Suction Hose

This heavy duty water suction hose is designed for use on portable pumps by contractors, quarries and mine sites.

Construction:

Tube: Black synthetic EPDM rubber

Reinforcement: Plies of polyester tire cord with wire helix

Cover: Smooth black weather and abrasion resistant rubber

Length: 100ft.

Temperature Range: -30° (-35°C) to +180°F (+82°C)



Part No.	I.D.	O.D.	Plies	WP psi	WT LBS/FT
2152BE-00750-00	¾	1.11	2	300	0.39
2152BE-01000-00	1	1.36	2	300	0.50
2152BE-01250-00	1¼	1.61	2	300	0.60
2152BE-01500-00	1½	1.86	2	250	0.70
2152BE-02000-00	2	2.43	2	200	1.13
2152BE-02500-00	2½	2.93	2	175	1.38
2152BE-03000-00	3	3.43	2	150	1.63
2152BE-03500-00	3½	3.99	2	125	2.37
2152BE-04000-00	4	4.49	2	100	2.70
2152BE-05000-00	5	5.58	2	100	4.31
2152BE-06000-00	6	6.65	2	75	5.81
2152BE-08000-00	8	8.74	2	75	8.36
2152BE-10000-00	10	10.85	2	75	13.47
2152BE-12000-00	12	12.95	4	75	17.52