

Novaflex 842 Multi-Purpose Exhaust & Fuel Fill Hose

Novaflex 842 is a multi-purpose marine hose designed to meet the requirements of J1527 A2, ISO 7840, USCG, NMMA & ABYC fuel fill hose requirements. It also meet the requirements of SAJ2006 R2 for marine exhaust hose.

842 is listed/meets SAE 1942-1 For use in vital water applications.

Construction:

Tube: Nitrile, black petroleum and heat resistant

Reinforcement: Plies of polyester fabric with wire helix

Cover: Black flame resistant, oil resistant

Length: 50 ft

Temperature Range: -30°F (-35°C) to +212°F (100°C)

Working pressure is 25% rated burst pressure



Novaflex 843 Multi-Purpose Exhaust & Fuel Fill Hose

Novaflex 843 is a multi-purpose marine hose designed to meet the requirements of J1527 A2, ISO 7840, USCG,

NMMA & ABYC fuel fill hose requirements. It also meet the requirements of SAJ2006 R2 for marine exhaust hose. 843 is listed/meets SAE 1942-1 For use in vital water applications.

Construction:

Tube: Nitrile, black petroleum and heat resistant

Reinforcement: Plies of polyester fabric with wire helix

Cover: Black flame resistant, oil resistant

Length: 50 ft

Temperature Range: -30°F (-35°C) to +212°F (100°C)



Part No	I.D.	Length	Max W.P.	MBR (in)
842BT-00500-00-600	1/2	50	50	2 1/2
842BT-00625-00-600	5/8	50	50	2 1/2
842BT-00750-00-600	3/4	50	50	2 1/2
842BT-00875-00-600	7/8	50	50	3
842BT-01000-00-600	1	50	50	3
842BT-01250-00-600	1 1/4	50	50	3
842BT-01375-00-600	1 3/8	50	50	4
842BT-01500-00-600	1 1/2	50	50	4
842BT-01625-00-600	1 5/8	50	50	5
842BT-01750-00-600	1 3/4	50	50	5
842BT-01875-00-600	1 7/8	50	50	5
842BT-02000-00-600	2	50	50	6
842BT-02125-00-600	2 1/8	50	50	6
842BT-02250-00-600	2 1/4	50	50	7
842BT-02375-00-600	2 3/8	50	50	7
842BT-02500-00-600	2 1/2	50	50	8
842BT-02625-00-600	2 5/8	50	50	9
842BT-02750-00-600	2 3/4	50	50	10
842BT-03875-00-600	2 7/8	50	50	11
842BT-03000-00-600	3	50	50	13
842BT-03125-00-600	3 1/8	50	35	15
842BT-03250-00-600	3 1/4	50	35	15 1/2
842BT-03500-00-600	3 1/2	50	35	15 1/2
842BT-04000-00-600	4	50	35	16
842BT-04500-00-600	4 1/2	50	35	18
842BT-05000-00-600	5	50	35	20
842BT-06000-00-600	6	50	35	24

Part No	I.D.	Length	Max W.P.	MBR (in)	WT LBS/FT
843-00500-00-600	1/2	50	150	1.5	.45
843-00625-00-600	5/8	50	150	2	.53
843-00750-00-600	3/4	50	150	2 1/2	.63
843-00875-00-600	7/8	50	150	3	.72
843-01000-00-600	1	50	150	3	.88
843-01250-00-600	1 1/4	50	150	4	.97
843-01375-00-600	1 3/8	50	150	4	1.62
843-01500-00-600	1 1/2	50	150	4.5	1.19
843-01625-00-600	1 5/8	50	150	5	1.28
843-01750-00-600	1 3/4	50	150	5	1.28
843-01875-00-600	1 7/8	50	150	5.5	1.36
843-02000-00-600	2	50	150	6	1.53
843-02125-00-600	2 1/8	50	150	6.5	1.62
843-02250-00-600	2 1/4	50	150	6.5	1.69
843-02375-00-600	2 3/8	50	150	7	1.78
843-02500-00-600	2 1/2	50	150	7.5	1.85
843-02625-00-600	2 5/8	50	150	7.5	1.93
843-02750-00-600	2 3/4	50	150	8.5	2.02
843-03875-00-600	2 7/8	50	150	8.5	2.09
843-03000-00-600	3	50	150	9	2.18
843-03125-00-600	3 1/8	50	150	9.5	2.27
843-03250-00-600	3 1/4	50	150	10	2.35
843-03500-00-600	3 1/2	50	150	10.5	2.51
843-04000-00-600	4	50	150	12	2.83
843-04500-00-600	4 1/2	50	150	13.5	3.50
843-05000-00-600	5	50	150	15	3.86
843-06000-00-600	6	50	150	18	4.57

Fuel Compatibility: Ethanol up to E85. Biodiesel up to B20

Fuel Compatibility: Ethanol up to E85. Biodiesel up to B20