

Marine Water & Exhaust Hose

Novaflex Series 149 PVC Live Well & Bilge Hose

Smooth ID & OD. Black PVC helix rod with black PVC tube.

Applications Include fill lines, drain lines, scupper drain lines, Live well and bilge pump lines. Excellent flexibility!

Construction:

Tube: Black PVC

Reinforcement: PVC helix rod

Length: 100 ft

Temperature Range: -20°F (-29°C) to +120°F (+49°C)



Part No	I.D.	O.D.	MBR (in)	VAC Rating	WT LBS/FT
149BL-00750-00	¾	3 ¹ / ₃₂	3	28	20
149BL-01000-00	1	1¼	3	28	27
149BL-01125-00	1⅞	1 ¹¹ / ₃₂	3	28	28
149BL-01250-00	1¼	1½	3½	28	33
149BL-01500-00	1½	1⅞	4	28	40
149BL-01875-00	1⅞	2¼	5½	28	52

Novaflex Series 150 Potable Water PVC Tubing Heavy Duty

Clear vinyl FDA PVC tubing for use in sink drains, potable water lines, ice boxes and refrigerators. Odorless and tasteless. Not recommended for hot water or below water line.

Construction:

Tube: Seamless clear PVC tube made with FDA ingredients that are NSF 51 certified USP Class VI Rated Materials. RoHS Compliant, US Government A-A-52047

Type VI Compliant EU:

Meets requirements of UL94 HB burn rating

Temperature Range: +25° (-4°C) to 150°F (+66°C)



Part No	I.D.	O.D.	WP (psi)	WT 100/FT
150CL-00250-00	¼	⅜	55	3.4 lbs
150CL-00625-00	⅜	½	40	4.8 lbs
150CL-00500-00	½	⅝	30	6.2 lbs
150CL-00625-00	⅝	1 ³ / ₁₆	35	12 lbs
150CL-07500-00	¾	1	35	19 lbs
150CL-01500-00	1	1¼	28	25 lbs
150CL-01250-00	1¼	1½	22	30.5 lbs

WP rating is at 70°F