

Novaflex 162 Red PVC Braided Hose with red trace yarn



Heavy duty clear PVC tube and cover with polyester reinforcement. Excellent for potable water and food transfer.

FDA-NSF 51 Certified to 100°F (+38°C)

Construction:

Tube: PVC clear

Reinforcement: Polyester

Cover: PVC Clear

Length: see coil length

Temperature Range: -20°F (-29°C) to +150°F (+66°C)

(WP pressures drop above 68°F (+20°C))

Part No.	I.D.	O.D.	Max WP @ 68°F	Length Coils	WT LBS/FT
162RL-00375-00	3/8	0.565	150	250	0.076
162RL-00500-00	1/2	0.70	150	250	0.103
162RL-00625-00	5/8	0.825	100	250	0.124
162RL-00750-00	3/4	0.95	100	250	0.145
162RL-01000-00	1	1.23	75	250	0.216
162RL-01250-00	1 1/4	1.55	70	100	0.298
162RL-01500-00	1 1/2	1.80	65	100	0.36

Novaflex 164 PVC Braided Hose with blue trace yarn



Heavy duty white PVC tube with polyester reinforcement. Excellent for potable water and food transfer where a clear hose is not desirable.

FDA-NSF 51 certified.

Construction:

Tube: White PVC

Reinforcement: Polyester

Cover: Clear PVC

Length: See coil length

Temperature Range: -20°F (-29°C) to +150°F (+66°C)

(WP pressures drop above 68°F (+20°C))

Part No.	I.D.	O.D.	Max WP @ 68°F	Length	WT LBS/FT
164LL-00375-00	3/8	0.565	150	250	0.076
164LL-00500-00	1/2	0.70	150	250	0.103
164LL-00750-00	3/4	0.95	100	250	0.145

Novaflex 200 Softwall Water/Exhaust Hose



Designed for a wide range of water transfer and discharge applications as well as the tough demands of wet exhaust. The softwall (non-wire) construction is designed for straight routings.

An excellent choice for bilge, toilet, scupper and water discharge applications that are straight. Meets SAE J2006R1 for marine exhaust hose.

Construction:

Tube: EPDM, Black

Reinforcement: Polyester fabric

Cover: EPDM, Black

Length: 50 ft

Temperature Range: -40°F (-21°C) to +250°F (+121°C)

Not for steam service

Part No.	I.D.	O.D.	Plies	WP psi	WT LBS/FT
200BE-01500-00	1 1/2	1.94	2	250	0.50
200BE-01625-00	1 5/8	2.06	2	250	0.54
200BE-01750-00	1 3/4	2.19	2	250	0.58
200BE-01875-00	1 7/8	2.31	2	250	0.63
200BE-02000-00	2	2.44	2	200	0.67
200BE-02125-00	2 1/8	2.69	2	200	0.91
200BE-02250-00	2 1/4	2.81	2	200	0.97
200BE-02375-00	2 3/8	2.94	2	200	1.02
200BE-02500-00	2 1/2	3.06	2	150	1.07
200BE-02625-00	2 5/8	3.19	2	150	1.13
200BE-21875-00	2 7/8	3.44	2	150	1.23
200BE-03000-00	3	3.56	2	125	1.29
200BE-03125-00	3 1/8	3.69	2	125	1.34
200BE-03500-00	3 1/2	4.06	2	125	1.50
200BE-04000-00	4	4.56	2	100	1.72
200BE-04125-00	4 1/8	4.69	2	100	1.77
200BE-04500-00	4 1/2	5.13	2	100	2.15
200BE-05000-00	5	5.63	2	100	2.38
200BE-05500-00	5 1/2	6.13	2	100	2.62
200BE-06000-00	6	6.63	2	85	2.86
200BE-06625-00	6 5/8	7.41	2	75	3.95
200BE-08000-00	8	8.78	2	75	4.76