

Novaflex 841 Heavy Duty Oil Resistant Soft Wall Exhaust Hose

This heavy duty marine softwall exhaust hose is an industry standard for use in oily applications. (Designed for straight applications). Meets SAE J2006.

Construction:

Tube: Nitrile
Reinforcement: Polyester tire cord
Cover: Black oil resistant
Length: 50 ft or 100 ft.
Temperature Range: -40°F (-40°C) to +210°F (+99°C)
Not for steam service



Part No.	I.D.	O.D.	Plies	WP psi	WT LBS/FT
841BN-00875-00	7/8	1.28	2	250	0.51
841BN-01000-00	1	1.41	2	250	0.56
841BN-01125-00	1 1/8	1.54	2	250	0.63
841BN-01250-00	1 1/4	1.66	2	225	0.69
841BN-01375-00	1 3/8	1.78	2	220	0.75
841BN-01500-00	1 1/2	1.96	2	200	0.89
841BN-01625-00	1 5/8	2.08	2	185	0.96
841BN-01750-00	1 3/4	2.26	2	175	1.11
841BN-01875-00	1 7/8	2.38	2	160	1.19
841BN-02000-00	2	2.50	2	150	1.25
841BN-02125-00	2 1/8	2.63	2	150	1.31
841BN-02250-00	2 1/4	2.76	2	140	1.38
841BN-02375-00	2 3/8	2.80	4	250	1.33
841BN-02500-00	2 1/2	3.07	4	250	1.80
841BN-02625-00	2 5/8	3.13	4	225	1.75
841BN-02750-00	2 3/4	3.31	4	220	1.98
841BN-02875-00	2 7/8	3.43	4	220	2.05
841BN-03000-00	3	3.54	4	210	2.07
841BN-03125-00	3 1/8	3.66	4	200	2.16
841BN-03250-00	3 1/4	3.80	4	190	2.29
841BN-03500-00	3 1/2	4.05	4	180	2.44
841BN-04000-00	4	4.60	4	150	3.11
841BN-04500-00	4 1/2	5.18	4	140	3.85
841BN-05000-00	5	5.69	4	130	4.31
841BN-05500-00	5 1/2	6.21	4	120	4.81
841BN-06000-00	6	6.74	4	110	5.48
841BN-06625-00	6 5/8	7.37	4	100	6.02
841BN-08652-00	8 5/8	9.38	4	100	7.05
841BN-10750-00	10 3/4	11.50	4	100	7.90
841BN-12750-00	12 3/4	13.50	4	100	9.18