

Novaflex 5164TG Tan Gum Tubing

Wrapped finish, mandrel made tan gum tubing designed for a variety of industrial, construction and chemical applications.



Construction:

Tube: Tan gum
Length: 50 ft
Temperature Range: -40°F (-40°C) to +140°F (+60°C)
Durometer: 42 durometer
Available in EPDM, SBR, Nitrile and Neoprene
A large variety of diameters available ranging from 1 1/4" to 24" upon request.

I.D.	3/16"	1/4"	3/8"	1/2"
	19	25	38	50
1 1/4	5164TG-01250-19	5164TG-01250-25	5164TG-01250-38	5164TG-01250-50
1 1/2	5164TG-01500-19	5164TG-01500-25	5164TG-01500-38	5164TG-01500-50
2	5164TG-02000-19	5164TG-02000-25	5164TG-02000-38	5164TG-02000-50
3	5164TG-03000-19	5164TG-03000-25	5164TG-03000-38	5164TG-03000-50
4	5164TG-04000-19	5164TG-04000-25	5164TG-04000-38	5164TG-04000-50
6	5164TG-06000-19	5164TG-06000-25	5164TG-06000-38	5164TG-06000-50
8	5164TG-08000-19	5164TG-08000-25	5164TG-08000-38	5164TG-08000-50
10	5164TG-10000-19	5164TG-10000-25	5164TG-10000-38	5164TG-10000-50
12	5164TG-12000-19	5164TG-12000-25	5164TG-12000-38	5164TG-12000-50
18*	5164TG-18000-19-306	5164TG-18000-25-306	5164TG-18000-38-306	5164TG-18000-50-306
20*	5164TG-20000-19-300	5164TG-20000-25-300	5164TG-20000-38-300	5164TG-20000-50-300
24*	5164TG-24000-19-300	5164TG-24000-25-300	5164TG-24000-38-300	5164TG-24000-50-300

**25ft. lengths, all other I.D's - 50ft lengths standard.
Cut lengths add 10% (5ft increments)*

Novaflex 5164BG Black Gum Tubing

Wrapped finish, mandrel made tan gum tubing designed for a variety of industrial, construction and chemical applications. Black gum rubber made for those applications where a black color is preferred.



Construction:

Tube: Black gum
Length: 50 ft
Temperature Range: Max temperature +160°F (+71°C)
Durometer: 50 durometer
Available in EPDM, SBR, Nitrile and Neoprene.
A large variety of diameters available ranging from 1 1/4" to 24" upon request.

ID	3/16"	1/4"	3/8"	1/2"
	19	25	38	50
1 1/4	5164BG-01250-19	5164BG-01250-25	5164BG-01250-38	5164BG-01250-50
1 1/2	5164BG-01500-19	5164BG-01500-25	5164BG-01500-38	5164BG-01500-50
2	5164BG-02000-19	5164BG-02000-25	5164BG-02000-38	5164BG-02000-50
3	5164BG-03000-19	5164BG-03000-25	5164BG-03000-38	5164BG-03000-50
4	5164BG-04000-19	5164BG-04000-25	5164BG-04000-38	5164BG-04000-50
6	5164BG-06000-19	5164BG-06000-25	5164BG-06000-38	5164BG-06000-50
8	5164BG-08000-19	5164BG-08000-25	5164BG-08000-38	5164BG-08000-50
10	5164BG-10000-19	5164BG-10000-25	5164BG-10000-38	5164BG-10000-50
12	5164BG-12000-19	5164BG-12000-25	5164BG-12000-38	5164BG-12000-50
18*	5164BG-18000-19	5164BG-18000-25	5164BG-18000-38	5164BG-18000-50
20*	5164BG-20000-19	5164BG-20000-25	5164BG-20000-38	5164BG-20000-50
24*	5164BG-24000-19	5164BG-24000-25	5164BG-24000-38	5164BG-24000-50

**25ft. lengths, all other I.D's - 50ft lengths standard.
Cut lengths add 10% (5ft increments)*

Novaflex 5164BE Black EPDM Gum Tubing

Wrapped finish, mandrel made tan gum tubing designed for a variety of industrial, construction and chemical applications. Black EPDM rubber, made for those applications where heat, chemical resistance and the properties of EPDM are preferable over gum rubber.



Construction:

Tube: Black gum
Length: 50 ft
Temperature Range: Max temperature +300°F (+149°C)
Durometer: 60 durometer
Available in EPDM, SBR, Nitrile and Neoprene.
A large variety of diameters available ranging from 1 1/4" to 24" upon request.

ID	3/16"	1/4"	3/8"	1/2"
	19	25	38	50
1 1/4	5164BE-01250-19	5164BE-01250-25	5164BE-01250-38	5164BE-01250-50
1 1/4	5164BE-01500-19	5164BE-01500-25	5164BE-01500-38	5164BE-01500-50
2	5164BE-02000-19	5164BE-02000-25	5164BE-02000-38	5164BE-02000-50
3	5164BE-03000-19	5164BE-03000-25	5164BE-03000-38	5164BE-03000-50
4	5164BE-04000-19	5164BE-04000-25	5164BE-04000-38	5164BE-04000-50
6	5164BE-06000-19	5164BE-06000-25	5164BE-06000-38	5164BE-06000-50
8	5164BE-08000-19	5164BE-08000-25	5164BE-08000-38	5164BE-08000-50
10	5164BE-10000-19	5164BE-10000-25	5164BE-10000-38	5164BE-10000-50
12	5164BE-12000-19	5164BE-12000-25	5164BE-12000-38	5164BE-12000-50
18*	5164BE-18000-19	5164BE-18000-25	5164BE-18000-38	5164BE-18000-50
20*	5164BE-20000-19	5164BE-20000-25	5164BE-20000-38	5164BE-20000-50
24*	5164BE-24000-19	5164BE-24000-25	5164BE-24000-38	5164BE-24000-50

**25ft. lengths, all other I.D's - 50ft lengths standard.
Cut lengths add 10% (5ft increments)*